

DJ LAND DEVELOPMENT

STORMWATER MANAGEMENT REPORT

PROPOSED DEVELOPMENT

SADDLER STREET EAST, DURHAM

MUNICIPALITY OF WEST GREY

JANUARY 2024

COBIDE Engineering Inc
517 10th Street
Hanover, ON N4N 1R4
TEL: 519-506-5959
www.cobideeng.com

TABLE OF CONTENTS

| | | |
|-----------|---|-----------|
| 1. | INTRODUCTION..... | 3 |
| 1.1 | Location | 3 |
| 1.2 | Development Proposal | 3 |
| 1.3 | Scope Of Work..... | 3 |
| 1.4 | Background Information | 4 |
| 2. | DRAINAGE CHARACTERISTICS | 6 |
| 2.1 | Regional | 6 |
| 2.2 | Local | 6 |
| 2.3 | Soils | 6 |
| 3. | STORMWATER CONTROL..... | 7 |
| 3.1 | Design Guidelines | 7 |
| 3.2 | Methodology for Computing Stormwater Runoff | 7 |
| 4. | EXISTING CONDITIONS | 8 |
| 4.1 | Pre-Development Catchment Areas | 8 |
| | Catchment Area 101 | 8 |
| | Catchment Area 102 | 8 |
| 5. | PROPOSED CONDITIONS..... | 9 |
| 5.1 | Post Development Catchment Areas | 9 |
| | Catchment Area 201 | 9 |
| | Catchment Area 202 | 9 |
| 6. | QUANTITY CONTROL | 10 |
| 6.1 | Design Requirements | 10 |
| 6.2 | SWM Facility Characteristics | 10 |
| 6.3 | SWM Facility Performance | 11 |
| 6.4 | Modelling Results..... | 11 |
| 6.4.1 | Discharge Point #1 | 11 |
| 6.4.2 | Discharge Point #2 | 12 |
| 6.4.3 | Modelling Summary..... | 12 |
| 7. | QUALITY CONTROL..... | 13 |
| 7.1 | Lot Level Control Measures | 13 |
| 7.2 | Conveyance Control Measures..... | 13 |
| 7.3 | End-of-Pipe Control Measures..... | 13 |

| | | |
|------------|--|-----------|
| 8. | EROSION & SEDIMENTATION CONTROL | 15 |
| 8.1 | Construction Stage | 15 |
| 8.2 | Lot Development | 15 |
| 8.3 | Restoration and Protection Measures | 15 |
| 9. | CONCLUSIONS & RECOMMENDATIONS | 16 |

LIST OF FIGURES

| | |
|------------------------------------|---|
| Figure 1 - Site Location Map | 5 |
|------------------------------------|---|

LIST OF TABLES

| | |
|--|----|
| Table 7.1 – SWM Facility Geometry | 10 |
| Table 7.2 – SWM Facility Performance | 11 |
| Table 7.3 – SWM Facility Performance | 11 |

APPENDICES

Appendix A – Drawings

- 01855 – DP1 – Draft Plan of Subdivision
- 01855 – SWM1 – Pre-Development Catchment Areas
- 01855 – SWM2 – Post Development Catchment Areas

Appendix B – Stormwater Management Modelling

- SWM Modelling – Pre and Post Development

Appendix C – Background Information

- Pre-Consultation Meeting Minutes

Appendix D – Design Details

- Oil Grit Separator (OGS)

1. INTRODUCTION

Cobide Engineering Inc. was retained by DJ Land Development to complete a preliminary stormwater management report in support of a Draft Plan Approval Application. The application will be to subdivide the property into a residential subdivision development.

A copy of the proposed Draft Plan has been included in **Appendix A** as Drawing 01855-DP1.

1.1 LOCATION

The proposed subdivision development, herein referred to as the Site, is located on Part of Park Lots 13, 14 and 15 on the North Side of Saddler Street, Registered Plan 500, within the Town of Durham, Municipality of West Grey, County of Grey. The Site is located on the north side of Saddler Street East between Rock Street and Concession 1. A Site Location Map is included as **Figure 1**.

1.2 DEVELOPMENT PROPOSAL

The overall property area is approximately 2.66 hectares (6.57 acres) in size. The owner is proposing to subdivide the property into 26 residential lots with a mix of semi-detached, four-plex and six-plex style units and condominium townhouse block consisting of 30 units. The subdivision will have two access points, one from Lambton Street East and one from Saddler Street East.

The development will consist of the following:

- Municipal Right-of-Way (Street A) providing access to Saddler Street East and Lambton Street East
- Lots 1 to 26 Semi-detached and Townhouse Units
- Block 28 Stormwater Management Facility
- Block 27 Condominium Townhouse Development
- Portion of land to be retained by owner to be sold to the adjacent landowner to the east due to existing encroachments

The Draft Plan showing the proposed development configuration has been included in **Appendix A** as Drawing 01855-DP1.

The Site is located on the southeast side of Durham and is currently zoned R1B and Future Development within the Municipality of West Grey's zoning. The property is within the primary settlement area in the current Grey County Official Plan.

1.3 SCOPE OF WORK

The stormwater management report addresses the design and implementation of drainage and stormwater management facilities for the development.

The report includes:

- Details of erosion protection and sedimentation control for short-term, construction phase and the long-term;
- Rehabilitation/protection measures;
- Quantity Control;
- Quality Control;


- Established lot grading requirements for the proposed site based on existing topographic constraints, neighbouring properties, groundwater elevations and overall proposed drainage patterns;
- Provisions for the major and minor flows through the development;
- Summary of Peak Flows, Stormwater Management Facility Geometry and Performance;
- Impact of stormwater drainage on County owned ditch along the south side of Lambton Street East;
- Summary of how all County, Municipal and Watershed SWM criteria has been satisfied.

1.4 BACKGROUND INFORMATION

In support of the Draft Plan Approval Application, pre-consultation with the Municipality of West Grey, County of Grey, and Saugeen Valley Conservation Authority (SVCA) has occurred. A copy of the pre-consultation meeting minutes has been included within **Appendix C** of this report.



MAP SOURCE - MTO ROAD MAP



517 - 10th STREET, Hanover, Ontario N4N 1R4
 Telephone: (519) 506-5959
 www.cobideeng.com

Client/Project
 PROPOSED RESIDENTIAL DEVELOPMENT
 SADDLER STREET EAST, DURHAM
 MUNICIPALITY OF WEST GREY
 COUNTY OF GREY
 STORMWATER MANAGEMENT REPORT

Figure No.

1

Title

REGIONAL LOCATION MAP

ORIGINAL SHEET - 8 x 11
 H:\Tremble\01855 Tremble Sadler St Townhouses\Drawings\Working Drawings\Regional Location.dwg Dec 18, 2023 - 10:38am
 COPYRIGHT © COBIDE ENGINEERING INC.

Figure 1 - Site Location Map

2. DRAINAGE CHARACTERISTICS

2.1 REGIONAL

The subject property is located within a large catchment area of approximately 34,640 hectares. The surface water drainage from this catchment occurs primarily overland from all directions, with the majority of the lands being upstream of the site towards the north and east flowing into the Saugeen River north and west of the property.

2.2 LOCAL

The majority of the surface runoff from the site currently flows from east to west towards the Saddler Street East Road allowance. The existing storm sewers along Saddler Street East convey the stormwater from the road allowance and residences with eventual outlet to the Saugeen River west of the site at the end of South Street West. A small portion of the north side of the site drains north into the existing roadside ditch along Lambton Street East which flows west into Durham Creek approximately 267m west of the proposed site access off Lambton Street East. Durham Creek meanders southwest towards the South Street West outlet into the Saugeen River.

There are no natural drainage courses that flow through the subject property. The topographical high point for the property is located at the upper southeast corner of the site, along the upper east boundary with an elevation of approximately 354.00 AMSL while the elevation at the southwest boundary of the site along Saddler Street East is approximately 349.50 metres AMSL. The average existing slope on the site is approximately 2.0%.

2.3 SOILS

The soil survey of Grey County (Report No. 17) identifies the native soils on the site as Sargent Loam which consists of a well sorted gravelly outwash. Sargent Loam is represented by Hydraulic Soil Group A. The surrounding properties consist of similar soil types including Donnybrook Loam which consists of sandy loam underlain by gravelly materials.

3. STORMWATER CONTROL

The design guidelines and constraints utilized in the stormwater management review for the development are as follows:

3.1 DESIGN GUIDELINES

The main design guideline utilized in this review is the Ministry of the Environment, Conservation and Parks (MECP) "*Stormwater Management Planning and Design (SWMP&D) Manual*," dated March 2003. Grey County's Stormwater Management Development Application Guidelines were also referenced when preparing this report.

The SWMP&D Manual details the methodologies for the preparation and evaluation of urban/suburban stormwater management measures. The document provides direction on the design of drainage/ stormwater management facilities required to meet the goals and objectives of the various Municipal/ Provincial Review Agencies.

The SWMP&D Manual provides information on the long-term operation and maintenance techniques for stormwater management facilities that may be implemented in the development of the subdivision.

The storm sewer design criteria to be used are as follows:

- Runoff from the 5 year storm is to be conveyed to a sufficient outlet via a combination of storm sewers and grass swales/ditches;
- Major storm runoff (i.e. >5 years) is to be contained within specified drainage corridors and not adversely impact any of the proposed units within the development or off-site properties.

3.2 METHODOLOGY FOR COMPUTING STORMWATER RUNOFF

As noted previously, the objectives of the Stormwater Management (SWM) Plan for development are to ensure that there is an adequate outlet to convey the runoff from the minor and major storm systems.

The objectives are to be achieved by completing the following tasks:

- i. Determining the existing drainage conditions;
- ii. Determining the post-development drainage conditions;
- iii. Design stormwater management measures that meet the criteria of the Municipality of West Grey, Ministry of Environment, Conservation and Parks (MECP), and Saugeen Valley Conservation Authority (SVCA).
- iv. Summarize the analysis by identifying conclusions and recommendations.

4. EXISTING CONDITIONS

The property is split into two main areas by the presence of the existing grassed, former rail trail that runs east to west across the top portion of the property. The north portion of the property consists of dense trees and a small portion of both maintained lawn and natural, unmaintained grassed areas. The south portion is a mixture of natural, unmaintained lawns and an area of maintained lawns along with a combination of trees and low-lying shrubs. The existing roadside ditch that is present along the north property boundary, (Lambton Street East), conveys the runoff from the north portion of the site. The south portion of the site is generally conveyed to the existing road allowance of Saddler Street East.

The pre-development catchment area boundaries are delineated on Drawing 01855-SWM1 attached in **Appendix A**.

Summarized below is a description of each catchment area.

4.1 PRE-DEVELOPMENT CATCHMENT AREAS

CATCHMENT AREA 101

- Includes all lands north of the former rail trail within the site boundary;
- Drainage is typically overland, sheet flow from the south to north towards the existing roadside ditch along the south side of Lambton Street East;
- Catchment Area 101 is considered to discharge to Discharge Point #1 for the purposes of this report;
- Approximately 1.10 ha in area.

CATCHMENT AREA 102

- Includes all lands south of the former rail trail within the site boundary as well as a portion of lands to the east of the site boundary;
- Lands to the east of the site boundary include rear lots of existing residential dwellings on Saddler Street East;
- Drainage is typically overland, sheet flow from east to west towards the southwest corner of the site boundary towards the Saddler Street East Road allowance;
- Catchment Area 102 is considered to discharge to Discharge Point #2 for the purposes of this report;
- Approximately 2.78 ha in area.

5. PROPOSED CONDITIONS

The proposed post development catchment area boundaries are delineated on Drawing 01855-SWM2 attached in **Appendix A**.

Summarized below is a description of each catchment area.

5.1 POST DEVELOPMENT CATCHMENT AREAS

CATCHMENT AREA 201

- This catchment area includes a portion of the proposed Street 'A' road allowance, a small portion of the rooftops for Unit 1 and 13, and the rear yards of proposed dwellings on the north side in Block 27;
- Minor flows from the Street 'A' road allowance will be captured by the storm sewer which will discharge into the proposed stormwater management facility;
- Major flows will flow overland, discharging into the existing roadside ditch along the south side of Lambton Street East;
- Catchment Area 201 is considered to discharge to Discharge Point #1 for the purposes of this report;
- Approximately 0.47 ha in area.

CATCHMENT AREA 202

- This catchment area includes all the lands within Catchment 102 and the majority of the land from Catchment 101;
- Minor flows will be captured by the storm sewer and major flows will flow overland, both discharging into the proposed stormwater management facility;
- Catchment Area 202 is considered to discharge to Discharge Point #2 for the purposes of this report;
- Approximately 3.41 ha in area.

6. QUANTITY CONTROL

The hydrologic modelling software PCSWMM Version 5.6.1803 Professional 2D was used to determine the pre and post-development peak flows for the 2 yr., 5 yr., 25 yr., 50 yr., and 100 yr. storm events. The most current Environment Canada Data has been used for the modelling as it reflects more up to date data (2022 versus 2010) for the MTO parameters and provides a higher runoff rate thus providing a more conservative model. A copy of the rainfall data has been included with **Appendix B**.

The stormwater management design criteria for the subject site as recommended by the Municipality of West Grey, MECP and SVCA are to attenuate post-development peak flow rates to the pre-development levels for all storm events.

The pre-development and post development parameters and model outputs for all Catchments are contained in **Appendix B**.

6.1 DESIGN REQUIREMENTS

The intent of stormwater quantity control is to limit the flows under proposed conditions to existing levels or less to protect the downstream watercourses, infrastructure, and properties.

Minor flows from much of the development will be conveyed to the proposed stormwater management facility via a new storm sewer collection system that will be constructed throughout the development. This storm sewer collection system will be designed to accommodate all flows up to and including the 5 year storm event.

Major flows (>5 year), will be conveyed overland within the road allowance of the street.

Due to the increase in impervious area, stormwater quantity control will be required for the site. The design of the stormwater management facility has assumed a free outlet from the pond.

6.2 SWM FACILITY CHARACTERISTICS

The stormwater management facility and outlet structure have been designed to control peak runoff rates as well as conform to MECP best practices.

In order to provide the above required volumes and discharges, the following SWM facility geometry is being proposed:

Table 7.1 – SWM Facility Geometry

| SWM FACILITY | DETAILED DESIGN |
|----------------------|------------------------|
| Side Slope | 3:1 |
| SWM Facility Bottom | 346.75 m |
| Top Elevation | 349.50 m |
| High Water Elevation | 348.77 m |

The outlet configuration for the SWM Facility will be as follows:

- A 150 mm diameter orifice located at the pond bottom elevation of 346.75m.
- An emergency overflow spillway located on the south side of the pond will allow stormwater to drain from the pond during storm events larger than the 100 year storm if the primary outlet becomes blocked.

6.3 SWM FACILITY PERFORMANCE

Below is a summary of the hydraulic performance of the SWM facility during the various storm events:

Table 7.2 – SWM Facility Performance

| RETURN PERIOD | PEAK FLOW (l/s) | ELEVATION (m) | VOLUME (m ³) |
|---------------|-----------------|---------------|--------------------------|
| 2 Year | 42.4 | 347.52 | 288 |
| 5 Year | 51.7 | 347.86 | 469 |
| 25 Year | 63.1 | 348.36 | 805 |
| 50 Year | 67.2 | 348.57 | 961 |
| 100 Year | 70.9 | 348.77 | 1,127 |

6.4 MODELLING RESULTS

Based on the above outlet structure, the following summarizes the pre-development and post development peak flows to the two (2) discharge points:

Table 7.3 – SWM Peak Flow Summary

| RETURN PERIOD | DISCHARGE POINT #1 (l/s) | | DISCHARGE POINT #2 (l/s) | |
|---------------|--------------------------|---------------|--------------------------|---------------|
| | CATCHMENT 101 | CATCHMENT 201 | CATCHMENT 102 | CATCHMENT 202 |
| | PRE | POST | PRE | POST |
| 2 Year | 6.0 | 18.6 | 34.9 | 42.4 |
| 5 Year | 14.2 | 32.1 | 56.0 | 51.7 |
| 25 Year | 35.8 | 59.7 | 114.4 | 63.1 |
| 50 Year | 48.1 | 72.7 | 146.4 | 67.2 |
| 100 Year | 62.5 | 86.4 | 183.1 | 70.9 |

6.4.1 DISCHARGE POINT #1

As shown in the chart above, the pre-development flows are greater than the post development flows for Discharge Point #1. This is primarily due to the inability to grade the site in a manner that allows all the runoff to be directed towards the proposed SWM pond. Therefore, the post development flows to Lambton Street East are greater than the pre-development flows. The increase in flow is very minor and not expected to adversely impact any downstream infrastructure and properties between the site and Durham Creek.

6.4.2 DISCHARGE POINT #2

The post development flows for Discharge Point #2 are less than the pre-development flows for the majority of the storm events. The only storm event that is above the pre-development conditions is the 2-year storm event. This increase is not expected to cause any adverse impacts or issues as the storm sewers are designed to accommodate the 5-year storm event. Therefore, no additional quantity control beyond the construction of the proposed stormwater management facility is being considered.

6.4.3 MODELLING SUMMARY

Ultimately, both discharge points outlet to Durham Creek at Kincardine Street with eventual outlet to the Saugeen River. The combined post development flows are below the pre-development flows during all major storm events.

It is presumed that the downstream infrastructure from Rock Street West is adequate to service this proposed development as the current construction being completed by Grey County on Rock Street South of Saddler Street has been designed without stormwater controls. Based on the minor increases in flow as outlined above, it is not anticipated that this proposed development will negatively impact the existing downstream infrastructure.

7. QUALITY CONTROL

To meet the requirements of the Municipality of West Grey, MECP, and SVCA, stormwater quality control will be provided for the proposed development.

The MECP's SWMP&D Guidelines recommend that the required level of protection be associated with the habitat sensitivity of the receiving watercourse. The ultimate receiving watercourse for this development is the Saugeen River. For the purposes of this report, a 'Enhanced' water quality protection level will be implemented in accordance with the MECP 2003 Guidelines and SVCA requirements.

In keeping with the approach suggested in the SWMP&D manual, a 'treatment train' approach to stormwater quality management has been proposed for this development. This approach consists of three (3) levels of treatment which are described as follows:

- Lot level control measures
- Conveyance control measures
- End-of-Pipe control measures

A review of each measure and its suitability for use in the development is discussed below:

7.1 LOT LEVEL CONTROL MEASURES

The Municipality of West Grey design standards require minimum grades of 2.0% for lot grading, driveways, and drainage swales. Therefore, reduced lot grading of the front, side, and rear yards to less than 2.0% is not feasible.

The north portion of the site contains karst deposits and therefore the use of drainage pits and infiltration trenches have not been considered. Drainage pits and infiltration trenches also require additional ongoing maintenance which is borne by the homeowner and their long-term function is contingent on the action of the landowner.

It is proposed that all runoff draining from rooftops be directed overland across the grass lawns to encourage infiltration and filtering of pollutants from this runoff. The Lot Grading Plan will note the following "Roof drain troughs shall be directed to grassed areas of the property and not to driveways or private drain connections".

7.2 CONVEYANCE CONTROL MEASURES

The Municipality's standard road cross section only allows for the use of curb and gutter in new urban type subdivisions. Therefore, the use of grass swales as a conveyance control measure for runoff from the subdivision streets cannot be implemented.

Grassed drainage swales may be proposed to be constructed in the rear yards of some of the lots. These swales will provide rear yard drainage for the proposed lots. Swales will have slopes of at least 2.0% where possible. This will assist with removing pollutants and sediment from the runoff prior to draining into the municipal storm sewer system.

All catchbasins and manholes within the subdivision will be provided with minimum 600 mm and 300 mm sumps respectively which will assist in removing a portion of the sediment contained in the runoff from the street.

7.3 END-OF-PIPE CONTROL MEASURES

The proposed stormwater management pond has been designed such that it can be provide a minor level of end of pipe control prior to its discharge into the municipal storm sewer. The proposed pond can provide adequate storage while allowing the stored water to be released back into the storm sewer system at a reduced rate which will prevent downstream flooding.

The use of an Oil Grit Separator (OGS) is a viable option for this development to provide "Enhanced" treatment for the stormwater. The OGS will be installed at the downstream end of the new storm sewer

system prior to discharging into the stormwater management pond. Runoff from the impervious road surface will be collected by the storm sewers and directed through the OGS which will remove pollutants and sediment prior to discharging into the drainage ditch. Design details for the OGS are attached in **Appendix D**.

8. EROSION & SEDIMENTATION CONTROL

8.1 CONSTRUCTION STAGE

The following are details regarding the erosion and sediment control measures to be implemented during construction:

- Placement of siltation fences in all areas where surface drainage flows over disturbed areas. Siltation fence shall remain erect until construction is completed and the upstream area is fully re-vegetated.
- The stormwater management pond should be constructed first to act as a sedimentation pond during construction;
- Placement of temporary rock check dams within swales and any other locations where a concentrated flow of runoff may occur. All proposed drainage swales are to be seeded during construction;
- Installation of filter cloth under all new and existing catchbasin grates until paving of the subdivision streets is completed;
- Mud mats will be placed at construction accesses to keep public roadways free from debris during the construction period.

Once the ground surface of the site has been stabilized, the rock check dams and siltation fences can then be removed.

During the construction phase, it is important to ensure that erosion/sediment control is in place to ensure against transport of sediment into the existing downstream drainage ditches.

8.2 LOT DEVELOPMENT

During individual construction of homes within the subdivision, siltation barriers are to be constructed, as appropriate, to prevent the erosion of materials into the proposed roadside ditches and storm sewer system. The siltation barriers can be the form of siltation fences or shallow excavated sediment traps in the direction of flow from the construction site to the proposed drainage system.

The proposed grading will not alter the existing grading along the perimeter of the property. Individual lot grading will be determined based on the development of each lot; therefore, the sediment control of each individual lot is up to the landowner constructing the dwelling.

8.3 RESTORATION AND PROTECTION MEASURES

Every effort will be made to restore all disturbed areas as soon as possible after the completion of construction and lot development. A synergistic approach during construction, lot development and post-construction will be used to ensure adequate restoration to the disturbed areas has been completed to provide appropriate protection measures. This will be achieved by allowing disturbed areas to revegetate before removing sediment and erosion control measures as to avoid their migration from the subject property to any to adjacent properties, infrastructure and/or the municipal right-of-way. When and where beneficial, interim and rough grading of the property shall be completed such that the drainage and runoff is contained on site or controlled to a positive outlet. Special care shall be taken to ensure that silt and sediment laden surface water does not enter any watercourses or environmentally sensitive areas, either overland or through the storm drainage system.

9. CONCLUSIONS & RECOMMENDATIONS

The above report presents the Preliminary Stormwater Management Plan in support of Draft Plan Approval Application for a residential subdivision development located in Durham. Based on the findings of this report, the following conclusions are made:

1. Stormwater quantity control will be provided by a dry pond SWM Facility with an outlet configuration as described previously.
2. Stormwater quantity control for the development will maintain or lower pre-development flows during storm events for the flows captured in Catchment 202 (Discharge Point #2).
3. Stormwater quality control for the development will be higher than pre-development flows during storm events for the flows captured in Catchment 201 (Discharge Point #1) with proposed discharge to Lambton Street East. This increase however, is not expected to cause downstream concerns;
4. Stormwater quality will be provided by a treatment train approach which will include lot level control, conveyance control and 'end-of-pipe' control measures.

Lot level control will be provided by directing most impervious areas not directly connected to the municipal storm sewer system, over vegetated areas and directing all rear yard drainage to grass swales prior to discharging into the proposed storm sewer system.

Conveyance control will be provided by and providing a minimum 600 mm sumps in all catchbasins and a minimum 300 mm sumps in all catchbasin manholes.

End-of-pipe control will be provided by the proposed stormwater management pond (SWM facility).

All three levels of the treatment train approach will be used for the development to provide an "Enhanced" Level of protection for the development.

Based on the above conclusions of this report, it is recommended that the above Stormwater Management Report for the proposed subdivision be submitted to the SVCA, Municipality of West Grey and Grey County as part of the Draft Plan Approval Application.

Sincerely,

COBIDE Engineering Inc.



Amy R.M. Hoffarth, E.I.T.



Travis Burnside, P.Eng.
Director





Appendix A

DRAWINGS

01855 – DP1 – DRAFT PLAN OF SUBDIVISION

01855 – SWM1 – PRE-DEVELOPMENT CATCHMENT AREAS

01855 – SWM2 – POST DEVELOPMENT CATCHMENT AREAS



DRAFT PLAN OF SUBDIVISION
 SADDLER ST. TOWNHOUSES
 PART OF PARK LOTS 13, 14 & 15
 NORTH SIDE OF SADDLER STREET
 REGISTERED PLAN 500
 TOWN OF DURHAM
 MUNICIPALITY OF WEST GREY
 COUNTY OF GREY

RELEVANT SITE INFORMATION

| | |
|---|------------------|
| SEMI-DETACHED RESIDENTIAL LOTS (6) (LOTS 1 TO 2, LOTS 11 TO 14) | 0.331 ha. |
| STREET TOWNHOUSE RESIDENTIAL LOTS (20) (LOTS 3 TO 10, LOTS 15 TO 26) | 0.696 ha. |
| MUNICIPAL STREET (STREET A) | 0.393 ha. |
| BLOCK 27 (MULTI-FAMILY UNIT DWELLING) | 1.018 ha. |
| BLOCK 28 (STORM WATER MANAGEMENT) | 0.123 ha. |
| TOTAL PROPOSED SUBDIVISION | 2.563 ha. |

ADDITIONAL INFORMATION REQUIRED UNDER SECTION 51(17) OF THE PLANNING ACT

| | |
|-----------------------------|---|
| a. AS SHOWN | g. AS SHOWN |
| b. AS SHOWN | h. MUNICIPAL WATER SUPPLY |
| c. AS SHOWN | i. SANDY SILT & GRAVEL |
| d. MULTI-FAMILY RESIDENTIAL | j. AS SHOWN |
| e. AS SHOWN | k. WATER, STORM SEWERS, SANITARY SEWERS, HYDRO, TELEPHONE |
| f. AS SHOWN | l. AS SHOWN |

SURVEYOR'S CERTIFICATE

I CERTIFY THAT:
 THE BOUNDARIES OF THE LANDS TO BE SUBDIVIDED
 AND THEIR RELATIONSHIP TO THE ADJACENT LANDS
 ARE CORRECTLY SHOWN.

JAMES LAWS O.L.S.
 VAN HARTEN SURVEYING INC.

OWNER'S CERTIFICATE

I, THE REGISTERED OWNER OF THESE LANDS, HEREBY
 AUTHORIZE COBIDE ENGINEERING INC. TO SUBMIT
 THIS DRAFT PLAN FOR APPROVAL.

DRAFT APPROVAL SIGNATURE BLOCK

APPROVED IN ACCORDANCE WITH SECTION 51(31) OF THE
 PLANNING ACT, RSO, 1990, CHAPTER P-13, AS AMENDED.

THIS _____ DAY OF _____, 20__

SECRETARY-TREASURER OF THE LAND DIVISION COMMITTEE
 COUNTY OF GREY

SCALE 1:500

| | | | | |
|-----|-----------|------------------|-----|------|
| No. | DATE | DESCRIPTION | BY | APPD |
| 1 | DEC 07/23 | FIRST SUBMISSION | JHL | TLB |
| | | REVISION / ISSUE | | |

PROPOSED SUBDIVISION
 REGISTERED PLAN 500
 TOWN OF DURHAM
 MUNICIPALITY OF WEST GREY

Client: TREMBLE

Design: TLB Scale: 1:500
 Drawn: JHL Approved:
 Checked: TLB
 Date: DEC 2023

DRAWING No. 01855-DP1

RESIDENTIAL 'R2' ZONE PROVISIONS

| | SEMI-DETACHED | STREET TOWNHOUSE | RESIDENTIAL 'R3' ZONE PROVISIONS (CLUSTER TOWNHOUSE) |
|-----------------------|---------------------------------------|------------------|--|
| LOT AREA (MIN.) | 275 sq.m. | 280 sq.m. | (SEE NOTE 2 BELOW) |
| LOT FRONTAGE (MIN.) | 9.0m | 6.5m | 20.1m |
| FRONT YARD (MIN.) | 7.6m | 7.5m | 7.6m |
| REAR YARD (MIN.) | 7.6m | 7.5m | 7.6m |
| EXT. SIDE YARD (MIN.) | 7.6m | 7.5m | 7.6m |
| INT. SIDE YARD (MIN.) | 1.2m & 1.8m & 3.7m (SEE NOTE 1 BELOW) | 3.0m | 6.0m |
| MAX. LOT COVERAGE | 45.0% | - | - |

NOTE:
 1) INTERIOR SIDE YARD REQUIREMENTS FOR A ONE STOREY UNIT IS 1.2m. MORE THAN ONE STOREY IS 1.8m. NO ATTACHED GARAGE IS 3.7m. EXCEPTING HOWEVER THAT THE SIDE YARD ALONG THE COMMON WALL DIVIDING THE ATTACHED UNITS SHALL BE 0m.
 2) LOT AREA MINIMUM:
 a) 1393.5 sq. m FOR THE FIRST FOUR UNITS.
 b) 264.8 sq. m FOR EACH ADDITIONAL UNIT THEREAFTER

SOURCE: MUNICIPALITY OF WEST GREY,
 ZONING BYLAW No. 37-2006 (INCLUDES AMENDMENTS IN FORCE AND EFFECT AS OF APRIL 1, 2017)

Lot Information



| Lot Number | Frontage (m) (AS DEFINED IN ZONING BY-LAW) | Area (sq.m) | Lot Coverage |
|------------|---|-------------|--------------|
| 1 | 17.8 | 659.1 | 24.2% |
| 2 | 12.7 | 414.4 | 38.6% |
| 3 | 12.7 | 387.4 | 41.2% |
| 4 | 9.1 | 277 | 49.3% |
| 5 | 9.1 | 277 | 49.3% |
| 6 | 12.7 | 384 | 41.6% |
| 7 | 12.7 | 384 | 41.6% |
| 8 | 9.1 | 277 | 49.3% |
| 9 | 9.1 | 277 | 49.3% |
| 10 | 12.7 | 419.2 | 38.1% |
| 11 | 19.8 | 656.3 | 38.4% |
| 12 | 19.8 | 656.9 | 38.3% |
| 13 | 18.5 | 570.9 | 28.0% |
| 14 | 16.7 | 470.6 | 34.0% |
| 15 | 16.7 | 512.2 | 31.2% |
| 16 | 9.1 | 280.5 | 48.8% |
| 17 | 9.1 | 280.2 | 48.8% |
| 18 | 12.7 | 388 | 41.2% |
| 19 | 12.7 | 387.5 | 41.2% |
| 20 | 9.1 | 279.2 | 48.8% |
| 21 | 9.1 | 278.9 | 48.8% |
| 22 | 12.7 | 386.2 | 41.2% |
| 23 | 12.7 | 385.7 | 41.2% |
| 24 | 9.1 | 277.9 | 48.8% |
| 25 | 9.1 | 277.7 | 48.8% |
| 26 | 18.4 | 569.1 | 28.1% |
| BLOCK 27 | - | 11163.3 | - |
| BLOCK 28 | - | 1233.6 | - |



H:\Tremble\01855 Tremble Sadder St Townhouses\Drawings\Submissions\2024-01-03 Preliminary Concept Plan\01855 Sadder St Townhouses 2024-01-03.dwg Jan 12, 2024 - 9:42am

CAUTION:
THE POSITION OF POLE LINES, CONDUITS, WATERMANS, SEWERS AND OTHER UNDERGROUND AND OVERGROUND UTILITIES AND STRUCTURES IS NOT NECESSARILY SHOWN ON THE DRAWINGS, AND, WHERE SHOWN, THE ACCURACY OF THE POSITION OF SUCH UTILITIES AND STRUCTURES IS NOT GUARANTEED. BEFORE STARTING WORK, THE CONTRACTOR SHALL INFORM THEMSELVES OF THE EXACT LOCATION OF ALL SUCH UTILITIES AND STRUCTURES, AND SHALL ASSUME ALL LIABILITY FOR DAMAGE TO THEM.

Notes



Benchmark Information
 BM1 SIB LOCATED AT NORTHEASTERN CORNER OF SUBJECT PROPERTY. ELEVATION 353.06m


| No. | DATE | DESCRIPTION | BY | APPD |
|------------------|------|-------------|----|------|
| REVISION / ISSUE | | | | |

Seal not valid unless signed and dated



**PROPOSED TOWNHOUSE DEVELOPMENT
 MUNICIPALITY OF WEST GREY
 COUNTY OF GREY
 PRE-DEVELOPMENT CATCHMENT AREAS**

Client: TREMBLE
 Design: TLB Scale: 1:500
 Drawn: ARMH Approved:
 Checked: TLB
 Date: NOV 2023
 DRAWING No. 01855-SWM1 Design Engineer





LEGEND

| | | | |
|-------|--------------------------------------|-----|---------------------------------------|
| --- | EXISTING STREET/PROPERTY LINES | --- | EXISTING CATCH BASIN |
| - - - | PROPOSED STREET/PROPERTY LINES | --- | EXISTING HYDRO GUY WIRE |
| --- | EDGE OF EXISTING PAVEMENT | --- | EXISTING HYDRO POLE |
| --- | EDGE OF EXISTING GRAVEL | --- | EXISTING TELEPHONE PEDESTAL |
| --- | EXISTING STORM SEWER | --- | STANDARD IRON BAR |
| --- | EXISTING FENCE | --- | IRON BAR |
| --- | EXISTING TREE LINE | --- | EXISTING DECIDUOUS TREE AND DIAMETER |
| --- | EXISTING UNDERGROUND TELEPHONE CABLE | --- | EXISTING CONIFEROUS TREE AND DIAMETER |
| --- | EXISTING UNDERGROUND GAS LINE | --- | BENCHMARK |
| --- | EXISTING UNDERGROUND HYDRO CABLE | --- | EXISTING CONTOUR |
| --- | EXISTING DITCH | --- | |
| --- | EXISTING MANHOLE | --- | |

H:\Tremble\01855 Tremble Saddler St Townhouses\Drawings\Submissions\2023-11-30 SWM\01855 Saddler St Townhouses Concept 2023-10-18.dwg

CAUTION: THE POSITION OF POLE LINES, CONDUITS, WATERMAINS, SEWERS AND OTHER UNDERGROUND AND OVERGROUND UTILITIES AND STRUCTURES IS NOT NECESSARILY SHOWN ON THE DRAWINGS. AND, WHERE SHOWN, THE ACCURACY OF THE POSITION OF SUCH UTILITIES AND STRUCTURES IS NOT GUARANTEED. BEFORE STARTING WORK, THE CONTRACTOR SHALL INFORM THEMSELVES OF THE EXACT LOCATION OF ALL SUCH UTILITIES AND STRUCTURES, AND SHALL ASSUME ALL LIABILITY FOR DAMAGE TO THEM.

Notes



Benchmark Information
 BM1 SIB LOCATED AT NORTHEASTERN CORNER OF SUBJECT PROPERTY. ELEVATION 353.06m

| No. | DATE | DESCRIPTION | BY | APPD |
|------------------|------|-------------|----|------|
| REVISION / ISSUE | | | | |

Seal not valid unless signed and dated



PROPOSED TOWNHOUSE DEVELOPMENT
 MUNICIPALITY OF WEST GREY
 COUNTY OF GREY
 POST DEVELOPMENT CATCHMENT AREAS

Client: TREMBLE

Design: TLB Scale: 1:500
 Drawn: ARMH Approved:
 Checked: TLB
 Date: NOV 2023

DRAWING No. 01855-SWM2



LEGEND


| | | | |
|-----|--------------------------------------|---|---------------------------------------|
| --- | EXISTING STREET/PROPERTY LINES | ○ | EXISTING CATCH BASIN |
| --- | PROPOSED STREET/PROPERTY LINES | ○ | EXISTING HYDRO GUY WIRE |
| --- | EDGE OF EXISTING PAVEMENT | ○ | EXISTING HYDRO POLE |
| --- | EDGE OF EXISTING GRAVEL | ○ | EXISTING TELEPHONE PEDESTAL |
| --- | EXISTING STORM SEWER | ○ | STANDARD IRON BAR |
| --- | EXISTING FENCE | ○ | IRON BAR |
| --- | EXISTING TREE LINE | ○ | EXISTING DECIDUOUS TREE AND DIAMETER |
| --- | EXISTING UNDERGROUND TELEPHONE CABLE | ○ | EXISTING CONIFEROUS TREE AND DIAMETER |
| --- | EXISTING UNDERGROUND GAS LINE | ○ | BENCHMARK |
| --- | EXISTING UNDERGROUND HYDRO CABLE | ○ | EXISTING CONTOUR |
| --- | EXISTING DITCH | ○ | |
| ○ | EXISTING MANHOLE | ○ | |

H:\Tremble\01855 Tremble Saddle S1 Townhouses\Drawings\Submissions\2023-11-30 SWM\01855 Saddle S1 Townhouses Concept 2023-10-18.dwg

Appendix B

**STORMWATER MANAGEMENT MODELLING
SWM MODELLING – PRE AND POST DEVELOPMENT**

Saddler Street Development - Model Schematic



SADDLER STREET DEVELOPMENT – SWM MODELLING – MODEL DETAILS

[TITLE]

```
;;Project Title/Notes
```

[OPTIONS]

```
;;Option Value
FLOW_UNITS LPS
INFILTRATION CURVE_NUMBER
FLOW_ROUTING DYNWAVE
LINK_OFFSETS ELEVATION
MIN_SLOPE 0
ALLOW_PONDING NO
SKIP_STEADY_STATE NO

START_DATE 12/2/2023
START_TIME 00:00:00
REPORT_START_DATE 12/2/2023
REPORT_START_TIME 00:00:00
END_DATE 12/3/2023
END_TIME 00:00:00
SWEEP_START 1/1
SWEEP_END 12/31
DRY_DAYS 0
REPORT_STEP 00:01:00
WET_STEP 00:05:00
DRY_STEP 00:05:00
ROUTING_STEP 5
RULE_STEP 00:00:00

INERTIAL_DAMPING PARTIAL
NORMAL_FLOW_LIMITED BOTH
FORCE_MAIN_EQUATION H-W
VARIABLE_STEP 0.75
LENGTHENING_STEP 0
MIN_SURFAREA 0
MAX_TRIALS 8
HEAD_TOLERANCE 0
SYS_FLOW_TOL 5
LAT_FLOW_TOL 5
MINIMUM_STEP 0.5
THREADS 8
```

[EVAPORATION]

```
;;Data Source Parameters
;;-----
CONSTANT 0.0
DRY_ONLY NO
```

[RAINGAGES]

```
;;Name Format Interval SCF Source
;;-----
SCS_Type_II_39.8mm_2yr INTENSITY 0:06 1.0 TIMESERIES SCS_Type_II_39.8mm_2yr
SCS_Type_II_55.1mm_5yr INTENSITY 0:06 1.0 TIMESERIES SCS_Type_II_55.1mm_5yr
SCS_Type_II_78.1mm_25yr INTENSITY 0:06 1.0 TIMESERIES SCS_Type_II_78.1mm_25yr
SCS_Type_II_87.6mm_50yr INTENSITY 0:06 1.0 TIMESERIES SCS_Type_II_87.6mm_50yr
SCS_Type_II_97.1mm_100yr INTENSITY 0:06 1.0 TIMESERIES SCS_Type_II_97.1mm_100yr
```

[SUBCATCHMENTS]

```
;;Name Rain Gage Outlet Area %Imperv Width %Slope CurbLen SnowPack
;;-----
101 SCS_Type_II_97.1mm_100yr Pre_CtyRd 1.1 0.8 212 1.7 0
102 SCS_Type_II_97.1mm_100yr Pre_Saddler 2.78 4.9 330 1.6 0
201 SCS_Type_II_97.1mm_100yr PostCtyRd 0.47 12.5 212 2.8 0
202 SCS_Type_II_97.1mm_100yr SU1 3.41 32.7 1100 2.5 0
```

[SUBAREAS]

```
;;Subcatchment N-Imperv N-Perv S-Imperv S-Perv PctZero RouteTo PctRouted
;;-----
101 0.01 0.37 0.05 0.05 25 OUTLET
102 0.01 0.31 0.05 0.05 25 OUTLET
201 0.01 0.25 0.05 0.05 25 OUTLET
202 0.01 0.25 0.05 0.05 25 OUTLET
```

[INFILTRATION]

SADDLER STREET DEVELOPMENT – SWM MODELLING – MODEL DETAILS

```

;;Subcatchment  Param1  Param2  Param3  Param4  Param5
-----
101             52.1    12.7    7        0        0
102             55.4    12.7    7        0        0
201             60      12.7    7        0        0
202             60      12.7    7        0        0

[OUTFALLS]
;;Name          Elevation  Type      Stage Data  Gated      Route To
-----
Post_Saddler    0          FREE
PostCtyRd       0          FREE
Pre_CtyRd       0          FREE
Pre_Saddler     0          FREE

[STORAGE]
;;Name          Elev.      MaxDepth  InitDepth  Shape      Curve Name/Params  SurDepth  Fevap  Psi
Ksat            IMD
-----
SU1             346.75    2.75     0          TABULAR    Pond                0          0

[ORIFICES]
;;Name          From Node  To Node   Type       Offset     Qcoeff      Gated      CloseTime
-----
OR1             SU1       Post_Saddler  SIDE      346.75    0.65       NO         0

[XSECTIONS]
;;Link          Shape      Geom1     Geom2     Geom3     Geom4     Barrels    Culvert
-----
OR1             CIRCULAR  0.15     0         0         0

[CURVES]
;;Name          Type      X-Value   Y-Value
-----
Pond            Storage  0         260
Pond            2.75    1075

[TIMESERIES]
;;Name          Date      Time      Value
-----
;SCS_Type_II_39.8mm design storm, total rainfall = 39.8 mm, rain interval = 6 minutes, rain units = mm/hr.
SCS_Type_II_39.8mm_2yr

;SCS_Type_II_55.1mm design storm, total rainfall = 55.1 mm, rain interval = 6 minutes, rain units = mm/hr.
SCS_Type_II_55.1mm_5yr

;SCS_Type_II_78.1mm design storm, total rainfall = 78.1 mm, rain interval = 6 minutes, rain units = mm/hr.
SCS_Type_II_78.1mm_25yr

;SCS_Type_II_87.6mm design storm, total rainfall = 87.6 mm, rain interval = 6 minutes, rain units = mm/hr.
SCS_Type_II_87.6mm_50yr

;SCS_Type_II_97.1mm design storm, total rainfall = 97.1 mm, rain interval = 6 minutes, rain units = mm/hr.
SCS_Type_II_97.1mm_100yr

[REPORT]
;;Reporting Options
INPUT          YES
CONTROLS      NO
SUBCATCHMENTS ALL
NODES ALL
LINKS ALL

[TAGS]

[MAP]
DIMENSIONS    515119.6099    4891364.6717    515754.9501    4891624.1243
UNITS         Meters
    
```

SADDLER STREET DEVELOPMENT – SWM MODELLING – 2 YEAR DESIGN STORM

EPA STORM WATER MANAGEMENT MODEL - VERSION 5.2 (Build 5.2.4)

Element Count

Number of rain gages 5
 Number of subcatchments ... 4
 Number of nodes 5
 Number of links 1
 Number of pollutants 0
 Number of land uses 0

Raingage Summary

| Name | Data Source | Data Type | Recording Interval |
|--------------------------|--------------------------|-----------|--------------------|
| SCS_Type_II_39.8mm_2yr | SCS_Type_II_39.8mm_2yr | INTENSITY | 6 min. |
| SCS_Type_II_55.1mm_5yr | SCS_Type_II_55.1mm_5yr | INTENSITY | 6 min. |
| SCS_Type_II_78.1mm_25yr | SCS_Type_II_78.1mm_25yr | INTENSITY | 6 min. |
| SCS_Type_II_87.6mm_50yr | SCS_Type_II_87.6mm_50yr | INTENSITY | 6 min. |
| SCS_Type_II_97.1mm_100yr | SCS_Type_II_97.1mm_100yr | INTENSITY | 6 min. |

Subcatchment Summary

| Name | Area | Width | %Imperv | %Slope | Rain Gage | Outlet |
|------|------|---------|---------|--------|------------------------|-------------|
| 101 | 1.10 | 212.00 | 0.80 | 1.7000 | SCS_Type_II_39.8mm_2yr | Pre_CtyRd |
| 102 | 2.78 | 330.00 | 4.90 | 1.6000 | SCS_Type_II_39.8mm_2yr | Pre_Saddler |
| 201 | 0.47 | 212.00 | 12.50 | 2.8000 | SCS_Type_II_39.8mm_2yr | PostCtyRd |
| 202 | 3.41 | 1100.00 | 32.70 | 2.5000 | SCS_Type_II_39.8mm_2yr | SU1 |

Node Summary

| Name | Type | Invert Elev. | Max. Depth | Ponded Area | External Inflow |
|--------------|---------|--------------|------------|-------------|-----------------|
| Post_Saddler | OUTFALL | 0.00 | 0.00 | 0.0 | |
| PostCtyRd | OUTFALL | 0.00 | 0.00 | 0.0 | |
| Pre_CtyRd | OUTFALL | 0.00 | 0.00 | 0.0 | |
| Pre_Saddler | OUTFALL | 0.00 | 0.00 | 0.0 | |
| SU1 | STORAGE | 346.75 | 2.75 | 0.0 | |

Link Summary

| Name | From Node | To Node | Type | Length | %Slope | Roughness |
|------|-----------|--------------|---------|--------|--------|-----------|
| OR1 | SU1 | Post_Saddler | ORIFICE | | | |

Cross Section Summary

| Conduit | Shape | Full Depth | Full Area | Hyd. Rad. | Max. Width | No. of Barrels | Full Flow |
|---------|-------|------------|-----------|-----------|------------|----------------|-----------|
| | | | | | | | |

Analysis Options

Flow Units LPS

Process Models:

SADDLER STREET DEVELOPMENT – SWM MODELLING – 2 YEAR DESIGN STORM

```

Rainfall/Runoff ..... YES
RDII ..... NO
Snowmelt ..... NO
Groundwater ..... NO
Flow Routing ..... YES
Ponding Allowed ..... NO
Water Quality ..... NO
Infiltration Method ..... CURVE_NUMBER
Flow Routing Method ..... DYNWAVE
Surcharge Method ..... EXTRAN
Starting Date ..... 12/02/2023 00:00:00
Ending Date ..... 12/03/2023 00:00:00
Antecedent Dry Days ..... 0.0
Report Time Step ..... 00:01:00
Wet Time Step ..... 00:05:00
Dry Time Step ..... 00:05:00
Routing Time Step ..... 5.00 sec
Variable Time Step ..... YES
Maximum Trials ..... 8
Number of Threads ..... 1
Head Tolerance ..... 0.001524 m
    
```

| | Volume hectare-m | Depth mm |
|----------------------------|---------------------|-------------|
| Runoff Quantity Continuity | | |
| Total Precipitation | 0.309 | 39.800 |
| Evaporation Loss | 0.000 | 0.000 |
| Infiltration Loss | 0.216 | 27.809 |
| Surface Runoff | 0.092 | 11.859 |
| Final Storage | 0.001 | 0.137 |
| Continuity Error (%) | -0.014 | |

| | Volume hectare-m | Volume 10^6 ltr |
|-----------------------------|---------------------|--------------------|
| Flow Routing Continuity | | |
| Dry Weather Inflow | 0.000 | 0.000 |
| Wet Weather Inflow | 0.092 | 0.921 |
| Groundwater Inflow | 0.000 | 0.000 |
| RDII Inflow | 0.000 | 0.000 |
| External Inflow | 0.000 | 0.000 |
| External Outflow | 0.092 | 0.920 |
| Flooding Loss | 0.000 | 0.000 |
| Evaporation Loss | 0.000 | 0.000 |
| Exfiltration Loss | 0.000 | 0.000 |
| Initial Stored Volume | 0.000 | 0.000 |
| Final Stored Volume | 0.000 | 0.001 |
| Continuity Error (%) | 0.000 | |

Time-Step Critical Elements
None

Highest Flow Instability Indexes
All links are stable.

Most Frequent Nonconverging Nodes
Convergence obtained at all time steps.

Routing Time Step Summary
Minimum Time Step : 4.50 sec
Average Time Step : 5.00 sec

SADDLER STREET DEVELOPMENT – SWM MODELLING – 2 YEAR DESIGN STORM

```

Maximum Time Step      :      5.00 sec
% of Time in Steady State :      0.00
Average Iterations per Step :      2.00
% of Steps Not Converging :      0.00
Time Step Frequencies :
  5.000 - 3.155 sec   :    100.00 %
  3.155 - 1.991 sec   :      0.00 %
  1.991 - 1.256 sec   :      0.00 %
  1.256 - 0.792 sec   :      0.00 %
  0.792 - 0.500 sec   :      0.00 %
  
```

Subcatchment Runoff Summary

| Peak Runoff | Runoff Coeff | Total Precip | Total Runon | Total Evap | Total Infil | Imperv Runoff | Perv Runoff | Total Runoff | Total Runoff |
|--------------|--------------|--------------|-------------|------------|-------------|---------------|-------------|--------------|--------------|
| Subcatchment | | mm | mm | mm | mm | mm | mm | mm | 10^6 ltr |
| LPS | | | | | | | | | |
| 101 | | 39.80 | 0.00 | 0.00 | 34.37 | 0.32 | 4.93 | 5.25 | 0.06 |
| 6.01 | 0.132 | | | | | | | | |
| 102 | | 39.80 | 0.00 | 0.00 | 32.66 | 1.95 | 4.96 | 6.91 | 0.19 |
| 34.92 | 0.174 | | | | | | | | |
| 201 | | 39.80 | 0.00 | 0.00 | 28.20 | 4.98 | 6.57 | 11.55 | 0.05 |
| 18.59 | 0.290 | | | | | | | | |
| 202 | | 39.80 | 0.00 | 0.00 | 21.69 | 13.02 | 5.05 | 18.07 | 0.62 |
| 269.58 | 0.454 | | | | | | | | |

Node Depth Summary

| Node | Type | Average Depth | Maximum Depth | Maximum HGL | Time of Max Occurrence | Reported Max Depth |
|--------------|---------|---------------|---------------|-------------|------------------------|--------------------|
| | | Meters | Meters | Meters | days hr:min | Meters |
| Post_Saddler | OUTFALL | 0.00 | 0.00 | 0.00 | 0 00:00 | 0.00 |
| PostCtyRd | OUTFALL | 0.00 | 0.00 | 0.00 | 0 00:00 | 0.00 |
| Pre_CtyRd | OUTFALL | 0.00 | 0.00 | 0.00 | 0 00:00 | 0.00 |
| Pre_Saddler | OUTFALL | 0.00 | 0.00 | 0.00 | 0 00:00 | 0.00 |
| SU1 | STORAGE | 0.11 | 0.77 | 347.52 | 0 03:31 | 0.77 |

Node Inflow Summary

| Node | Type | Maximum Lateral Inflow | Maximum Total Inflow | Time of Max Occurrence | Lateral Inflow Volume | Total Inflow Volume | Flow Balance Error |
|--------------|---------|------------------------|----------------------|------------------------|-----------------------|---------------------|--------------------|
| | | LPS | LPS | days hr:min | 10^6 ltr | 10^6 ltr | Percent |
| Post_Saddler | OUTFALL | 0.00 | 42.39 | 0 03:31 | 0 | 0.616 | 0.000 |
| PostCtyRd | OUTFALL | 18.59 | 18.59 | 0 03:00 | 0.0543 | 0.0543 | 0.000 |
| Pre_CtyRd | OUTFALL | 6.01 | 6.01 | 0 03:06 | 0.0578 | 0.0578 | 0.000 |
| Pre_Saddler | OUTFALL | 34.92 | 34.92 | 0 03:00 | 0.192 | 0.192 | 0.000 |
| SU1 | STORAGE | 269.58 | 269.58 | 0 03:00 | 0.617 | 0.617 | 0.000 |

Node Surcharge Summary

No nodes were surcharged.

SADDLER STREET DEVELOPMENT – SWM MODELLING – 2 YEAR DESIGN STORM

Node Flooding Summary

No nodes were flooded.

Storage Volume Summary

| Storage Unit | Average Volume 1000 m ³ | Avg Pcmt Full | Evap Pcmt Loss | Exfil Pcmt Loss | Maximum Volume 1000 m ³ | Max Pcmt Full | Time of Max Occurrence days hr:min | Maximum Outflow LPS |
|--------------|---------------------------------------|---------------|----------------|-----------------|---------------------------------------|---------------|---------------------------------------|------------------------|
| SU1 | 0.038 | 2.1 | 0.0 | 0.0 | 0.288 | 15.7 | 0 03:31 | 42.39 |

Outfall Loading Summary

| Outfall Node | Flow Freq Pcmt | Avg Flow LPS | Max Flow LPS | Total Volume 10 ⁶ ltr |
|--------------|----------------|--------------|--------------|-------------------------------------|
| Post_Saddler | 93.87 | 7.59 | 42.39 | 0.616 |
| PostCtyRd | 42.68 | 1.46 | 18.59 | 0.054 |
| Pre_CtyRd | 96.78 | 0.69 | 6.01 | 0.058 |
| Pre_Saddler | 99.97 | 2.23 | 34.92 | 0.192 |
| System | 83.33 | 11.97 | 93.72 | 0.920 |

Link Flow Summary

| Link | Type | Maximum Flow LPS | Time of Max Occurrence days hr:min | Maximum Veloc m/sec | Max/ Full Flow | Max/ Full Depth |
|------|---------|--------------------|---------------------------------------|-----------------------|----------------|-----------------|
| OR1 | ORIFICE | 42.39 | 0 03:31 | | | 1.00 |

Flow Classification Summary

| Conduit | Adjusted /Actual Length | Fraction of Time in Flow Class | | | | | | | | |
|---------|-------------------------|--------------------------------|-----|------|------|------|------|------|----------|------------|
| | | Up | | Down | | Sub | | Sup | | |
| | | Dry | Dry | Dry | Crit | Crit | Crit | Crit | Norm Ltd | Inlet Ctrl |
| | | | | | | | | | | |

Conduit Surcharge Summary

No conduits were surcharged.

Analysis begun on: Fri Dec 8 16:42:24 2023
Analysis ended on: Fri Dec 8 16:42:24 2023
Total elapsed time: < 1 sec

SADDLER STREET DEVELOPMENT – SWM MODELLING – 5 YEAR DESIGN STORM

EPA STORM WATER MANAGEMENT MODEL - VERSION 5.2 (Build 5.2.4)

Element Count

Number of rain gages 5
Number of subcatchments ... 4
Number of nodes 5
Number of links 1
Number of pollutants 0
Number of land uses 0

Raingage Summary

| Name | Data Source | Data Type | Recording Interval |
|--------------------------|--------------------------|-----------|--------------------|
| SCS_Type_II_39.8mm_2yr | SCS_Type_II_39.8mm_2yr | INTENSITY | 6 min. |
| SCS_Type_II_55.1mm_5yr | SCS_Type_II_55.1mm_5yr | INTENSITY | 6 min. |
| SCS_Type_II_78.1mm_25yr | SCS_Type_II_78.1mm_25yr | INTENSITY | 6 min. |
| SCS_Type_II_87.6mm_50yr | SCS_Type_II_87.6mm_50yr | INTENSITY | 6 min. |
| SCS_Type_II_97.1mm_100yr | SCS_Type_II_97.1mm_100yr | INTENSITY | 6 min. |

Subcatchment Summary

| Name | Area | Width | %Imperv | %Slope | Rain Gage | Outlet |
|------|------|---------|---------|--------|------------------------|-------------|
| 101 | 1.10 | 212.00 | 0.80 | 1.7000 | SCS_Type_II_55.1mm_5yr | Pre_CtyRd |
| 102 | 2.78 | 330.00 | 4.90 | 1.6000 | SCS_Type_II_55.1mm_5yr | Pre_Saddler |
| 201 | 0.47 | 212.00 | 12.50 | 2.8000 | SCS_Type_II_55.1mm_5yr | PostCtyRd |
| 202 | 3.41 | 1100.00 | 32.70 | 2.5000 | SCS_Type_II_55.1mm_5yr | SU1 |

Node Summary

| Name | Type | Invert Elev. | Max. Depth | Ponded Area | External Inflow |
|--------------|---------|--------------|------------|-------------|-----------------|
| Post_Saddler | OUTFALL | 0.00 | 0.00 | 0.0 | |
| PostCtyRd | OUTFALL | 0.00 | 0.00 | 0.0 | |
| Pre_CtyRd | OUTFALL | 0.00 | 0.00 | 0.0 | |
| Pre_Saddler | OUTFALL | 0.00 | 0.00 | 0.0 | |
| SU1 | STORAGE | 346.75 | 2.75 | 0.0 | |

Link Summary

| Name | From Node | To Node | Type | Length | %Slope | Roughness |
|------|-----------|--------------|---------|--------|--------|-----------|
| OR1 | SU1 | Post_Saddler | ORIFICE | | | |

Cross Section Summary

| Conduit | Shape | Full Depth | Full Area | Hyd. Rad. | Max. Width | No. of Barrels | Full Flow |
|---------|-------|------------|-----------|-----------|------------|----------------|-----------|
| | | | | | | | |

Analysis Options

Flow Units LPS
Process Models:

SADDLER STREET DEVELOPMENT – SWM MODELLING – 5 YEAR DESIGN STORM

```

Rainfall/Runoff ..... YES
RDII ..... NO
Snowmelt ..... NO
Groundwater ..... NO
Flow Routing ..... YES
Ponding Allowed ..... NO
Water Quality ..... NO
Infiltration Method ..... CURVE_NUMBER
Flow Routing Method ..... DYNWAVE
Surcharge Method ..... EXTRAN
Starting Date ..... 12/02/2023 00:00:00
Ending Date ..... 12/03/2023 00:00:00
Antecedent Dry Days ..... 0.0
Report Time Step ..... 00:01:00
Wet Time Step ..... 00:05:00
Dry Time Step ..... 00:05:00
Routing Time Step ..... 5.00 sec
Variable Time Step ..... YES
Maximum Trials ..... 8
Number of Threads ..... 1
Head Tolerance ..... 0.001524 m
    
```

| | Volume hectare-m | Depth mm |
|----------------------------|---------------------|-------------|
| Runoff Quantity Continuity | | |
| Total Precipitation | 0.428 | 55.100 |
| Evaporation Loss | 0.000 | 0.000 |
| Infiltration Loss | 0.281 | 36.259 |
| Surface Runoff | 0.145 | 18.709 |
| Final Storage | 0.001 | 0.139 |
| Continuity Error (%) | -0.012 | |

| | Volume hectare-m | Volume 10^6 ltr |
|-----------------------------|---------------------|--------------------|
| Flow Routing Continuity | | |
| Dry Weather Inflow | 0.000 | 0.000 |
| Wet Weather Inflow | 0.145 | 1.453 |
| Groundwater Inflow | 0.000 | 0.000 |
| RDII Inflow | 0.000 | 0.000 |
| External Inflow | 0.000 | 0.000 |
| External Outflow | 0.145 | 1.453 |
| Flooding Loss | 0.000 | 0.000 |
| Evaporation Loss | 0.000 | 0.000 |
| Exfiltration Loss | 0.000 | 0.000 |
| Initial Stored Volume | 0.000 | 0.000 |
| Final Stored Volume | 0.000 | 0.001 |
| Continuity Error (%) | 0.000 | |

```

*****
Time-Step Critical Elements
*****
None
    
```

```

*****
Highest Flow Instability Indexes
*****
All links are stable.
    
```

```

*****
Most Frequent Nonconverging Nodes
*****
Convergence obtained at all time steps.
    
```

```

*****
Routing Time Step Summary
*****
Minimum Time Step      :      4.50 sec
Average Time Step      :      5.00 sec
    
```

SADDLER STREET DEVELOPMENT – SWM MODELLING – 5 YEAR DESIGN STORM

```

Maximum Time Step      :      5.00 sec
% of Time in Steady State :      0.00
Average Iterations per Step :      2.00
% of Steps Not Converging :      0.00
Time Step Frequencies :
  5.000 - 3.155 sec   :    100.00 %
  3.155 - 1.991 sec   :      0.00 %
  1.991 - 1.256 sec   :      0.00 %
  1.256 - 0.792 sec   :      0.00 %
  0.792 - 0.500 sec   :      0.00 %
    
```

 Subcatchment Runoff Summary

| Peak Runoff | Runoff Coeff | Total Precip | Total Runon | Total Evap | Total Infil | Imperv Runoff | Perv Runoff | Total Runoff | Total Runoff |
|--------------|--------------|--------------|-------------|------------|-------------|---------------|-------------|--------------|--------------|
| Subcatchment | | mm | mm | mm | mm | mm | mm | mm | 10^6 ltr |
| LPS | | | | | | | | | |
| 101 | | 55.10 | 0.00 | 0.00 | 45.27 | 0.44 | 9.19 | 9.63 | 0.11 |
| 14.21 | 0.175 | | | | | | | | |
| 102 | | 55.10 | 0.00 | 0.00 | 42.83 | 2.70 | 9.34 | 12.04 | 0.33 |
| 56.04 | 0.218 | | | | | | | | |
| 201 | | 55.10 | 0.00 | 0.00 | 36.38 | 6.89 | 11.78 | 18.67 | 0.09 |
| 32.14 | 0.339 | | | | | | | | |
| 202 | | 55.10 | 0.00 | 0.00 | 27.98 | 18.02 | 9.06 | 27.08 | 0.92 |
| 404.55 | 0.491 | | | | | | | | |

 Node Depth Summary

| Node | Type | Average Depth | Maximum Depth | Maximum HGL | Time of Max Occurrence | Reported Max Depth |
|--------------|---------|---------------|---------------|-------------|------------------------|--------------------|
| | | Meters | Meters | Meters | days hr:min | Meters |
| Post_Saddler | OUTFALL | 0.00 | 0.00 | 0.00 | 0 00:00 | 0.00 |
| PostCtyRd | OUTFALL | 0.00 | 0.00 | 0.00 | 0 00:00 | 0.00 |
| Pre_CtyRd | OUTFALL | 0.00 | 0.00 | 0.00 | 0 00:00 | 0.00 |
| Pre_Saddler | OUTFALL | 0.00 | 0.00 | 0.00 | 0 00:00 | 0.00 |
| SU1 | STORAGE | 0.19 | 1.11 | 347.86 | 0 03:40 | 1.11 |

 Node Inflow Summary

| Node | Type | Maximum Lateral Inflow | Maximum Total Inflow | Time of Max Occurrence | Lateral Inflow Volume | Total Inflow Volume | Flow Balance Error |
|--------------|---------|------------------------|----------------------|------------------------|-----------------------|---------------------|--------------------|
| | | LPS | LPS | days hr:min | 10^6 ltr | 10^6 ltr | Percent |
| Post_Saddler | OUTFALL | 0.00 | 51.70 | 0 03:40 | 0 | 0.924 | 0.000 |
| PostCtyRd | OUTFALL | 32.14 | 32.14 | 0 03:06 | 0.0879 | 0.0879 | 0.000 |
| Pre_CtyRd | OUTFALL | 14.21 | 14.21 | 0 03:06 | 0.106 | 0.106 | 0.000 |
| Pre_Saddler | OUTFALL | 56.04 | 56.04 | 0 03:00 | 0.335 | 0.335 | 0.000 |
| SU1 | STORAGE | 404.55 | 404.55 | 0 03:00 | 0.924 | 0.924 | 0.000 |

 Node Surcharge Summary

No nodes were surcharged.

SADDLER STREET DEVELOPMENT – SWM MODELLING – 5 YEAR DESIGN STORM

Node Flooding Summary

No nodes were flooded.

Storage Volume Summary

| Storage Unit | Average Volume 1000 m ³ | Avg Pcmt Full | Evap Pcmt Loss | Exfil Pcmt Loss | Maximum Volume 1000 m ³ | Max Pcmt Full | Time of Max Occurrence days hr:min | Maximum Outflow LPS |
|--------------|---------------------------------------|---------------|----------------|-----------------|---------------------------------------|---------------|---------------------------------------|------------------------|
| SU1 | 0.071 | 3.9 | 0.0 | 0.0 | 0.469 | 25.6 | 0 03:40 | 51.70 |

Outfall Loading Summary

| Outfall Node | Flow Freq Pcmt | Avg Flow LPS | Max Flow LPS | Total Volume 10 ⁶ ltr |
|--------------|----------------|--------------|--------------|-------------------------------------|
| Post_Saddler | 96.23 | 11.11 | 51.70 | 0.924 |
| PostCtyRd | 43.85 | 2.31 | 32.14 | 0.088 |
| Pre_CtyRd | 98.56 | 1.25 | 14.21 | 0.106 |
| Pre_Saddler | 99.98 | 3.88 | 56.04 | 0.335 |
| System | 84.66 | 18.54 | 148.64 | 1.453 |

Link Flow Summary

| Link | Type | Maximum Flow LPS | Time of Max Occurrence days hr:min | Maximum Veloc m/sec | Max/ Full Flow | Max/ Full Depth |
|------|---------|--------------------|---------------------------------------|-----------------------|----------------|-----------------|
| OR1 | ORIFICE | 51.70 | 0 03:40 | | | 1.00 |

Flow Classification Summary

| Conduit | Adjusted /Actual Length | Fraction of Time in Flow Class | | | | | | | | |
|---------|-------------------------|--------------------------------|--------|----------|----------|----------|---------|-----------|----------|------------|
| | | Dry | Up Dry | Down Dry | Sub Crit | Sup Crit | Up Crit | Down Crit | Norm Ltd | Inlet Ctrl |
| | | | | | | | | | | |

Conduit Surcharge Summary

No conduits were surcharged.

Analysis begun on: Wed Jan 17 20:46:34 2024
Analysis ended on: Wed Jan 17 20:46:34 2024
Total elapsed time: < 1 sec

SADDLER STREET DEVELOPMENT – SWM MODELLING – 25 YEAR DESIGN STORM

EPA STORM WATER MANAGEMENT MODEL - VERSION 5.2 (Build 5.2.4)

 Element Count

Number of rain gages 5
 Number of subcatchments ... 4
 Number of nodes 5
 Number of links 1
 Number of pollutants 0
 Number of land uses 0

 Raingage Summary

| Name | Data Source | Data Type | Recording Interval |
|--------------------------|--------------------------|-----------|--------------------|
| SCS_Type_II_39.8mm_2yr | SCS_Type_II_39.8mm_2yr | INTENSITY | 6 min. |
| SCS_Type_II_55.1mm_5yr | SCS_Type_II_55.1mm_5yr | INTENSITY | 6 min. |
| SCS_Type_II_78.1mm_25yr | SCS_Type_II_78.1mm_25yr | INTENSITY | 6 min. |
| SCS_Type_II_87.6mm_50yr | SCS_Type_II_87.6mm_50yr | INTENSITY | 6 min. |
| SCS_Type_II_97.1mm_100yr | SCS_Type_II_97.1mm_100yr | INTENSITY | 6 min. |

 Subcatchment Summary

| Name | Area | Width | %Imperv | %Slope | Rain Gage | Outlet |
|------|------|---------|---------|--------|-------------------------|-------------|
| 101 | 1.10 | 212.00 | 0.80 | 1.7000 | SCS_Type_II_78.1mm_25yr | Pre_CtyRd |
| 102 | 2.78 | 330.00 | 4.90 | 1.6000 | SCS_Type_II_78.1mm_25yr | Pre_Saddler |
| 201 | 0.47 | 212.00 | 12.50 | 2.8000 | SCS_Type_II_78.1mm_25yr | PostCtyRd |
| 202 | 3.41 | 1100.00 | 32.70 | 2.5000 | SCS_Type_II_78.1mm_25yr | SU1 |

 Node Summary

| Name | Type | Invert Elev. | Max. Depth | Ponded Area | External Inflow |
|--------------|---------|--------------|------------|-------------|-----------------|
| Post_Saddler | OUTFALL | 0.00 | 0.00 | 0.0 | |
| PostCtyRd | OUTFALL | 0.00 | 0.00 | 0.0 | |
| Pre_CtyRd | OUTFALL | 0.00 | 0.00 | 0.0 | |
| Pre_Saddler | OUTFALL | 0.00 | 0.00 | 0.0 | |
| SU1 | STORAGE | 346.75 | 2.75 | 0.0 | |

 Link Summary

| Name | From Node | To Node | Type | Length | %Slope | Roughness |
|------|-----------|--------------|---------|--------|--------|-----------|
| OR1 | SU1 | Post_Saddler | ORIFICE | | | |

 Cross Section Summary

| Conduit | Shape | Full Depth | Full Area | Hyd. Rad. | Max. Width | No. of Barrels | Full Flow |
|---------|-------|------------|-----------|-----------|------------|----------------|-----------|
| | | | | | | | |

 Analysis Options

Flow Units LPS
 Process Models:

SADDLER STREET DEVELOPMENT – SWM MODELLING – 25 YEAR DESIGN STORM

```

Rainfall/Runoff ..... YES
RDII ..... NO
Snowmelt ..... NO
Groundwater ..... NO
Flow Routing ..... YES
Ponding Allowed ..... NO
Water Quality ..... NO
Infiltration Method ..... CURVE_NUMBER
Flow Routing Method ..... DYNWAVE
Surcharge Method ..... EXTRAN
Starting Date ..... 12/02/2023 00:00:00
Ending Date ..... 12/03/2023 00:00:00
Antecedent Dry Days ..... 0.0
Report Time Step ..... 00:01:00
Wet Time Step ..... 00:05:00
Dry Time Step ..... 00:05:00
Routing Time Step ..... 5.00 sec
Variable Time Step ..... YES
Maximum Trials ..... 8
Number of Threads ..... 1
Head Tolerance ..... 0.001524 m
    
```

| | Volume hectare-m | Depth mm |
|----------------------------|---------------------|-------------|
| Runoff Quantity Continuity | | |
| Total Precipitation | 0.606 | 78.100 |
| Evaporation Loss | 0.000 | 0.000 |
| Infiltration Loss | 0.366 | 47.163 |
| Surface Runoff | 0.239 | 30.807 |
| Final Storage | 0.001 | 0.142 |
| Continuity Error (%) | -0.014 | |

| | Volume hectare-m | Volume 10^6 ltr |
|-----------------------------|---------------------|--------------------|
| Flow Routing Continuity | | |
| Dry Weather Inflow | 0.000 | 0.000 |
| Wet Weather Inflow | 0.239 | 2.394 |
| Groundwater Inflow | 0.000 | 0.000 |
| RDII Inflow | 0.000 | 0.000 |
| External Inflow | 0.000 | 0.000 |
| External Outflow | 0.239 | 2.393 |
| Flooding Loss | 0.000 | 0.000 |
| Evaporation Loss | 0.000 | 0.000 |
| Exfiltration Loss | 0.000 | 0.000 |
| Initial Stored Volume | 0.000 | 0.000 |
| Final Stored Volume | 0.000 | 0.001 |
| Continuity Error (%) | 0.000 | |

```

*****
Time-Step Critical Elements
*****
None
    
```

```

*****
Highest Flow Instability Indexes
*****
All links are stable.
    
```

```

*****
Most Frequent Nonconverging Nodes
*****
Convergence obtained at all time steps.
    
```

```

*****
Routing Time Step Summary
*****
Minimum Time Step      :      4.50 sec
Average Time Step      :      5.00 sec
    
```

SADDLER STREET DEVELOPMENT – SWM MODELLING – 25 YEAR DESIGN STORM

```

Maximum Time Step      :      5.00 sec
% of Time in Steady State :      0.00
Average Iterations per Step :      2.00
% of Steps Not Converging :      0.00
Time Step Frequencies :
  5.000 - 3.155 sec   :    100.00 %
  3.155 - 1.991 sec   :      0.00 %
  1.991 - 1.256 sec   :      0.00 %
  1.256 - 0.792 sec   :      0.00 %
  0.792 - 0.500 sec   :      0.00 %
  
```

 Subcatchment Runoff Summary

| Peak Runoff | Runoff Coeff | Total Precip | Total Runon | Total Evap | Total Infil | Imperv Runoff | Perv Runoff | Total Runoff | Total Runoff |
|--------------|--------------|--------------|-------------|------------|-------------|---------------|-------------|--------------|--------------|
| Subcatchment | | mm | mm | mm | mm | mm | mm | mm | 10^6 ltr |
| LPS | | | | | | | | | |
| 101 | | 78.10 | 0.00 | 0.00 | 59.65 | 0.62 | 17.63 | 18.25 | 0.20 |
| 35.77 | 0.234 | | | | | | | | |
| 102 | | 78.10 | 0.00 | 0.00 | 55.89 | 3.83 | 18.14 | 21.97 | 0.61 |
| 114.36 | 0.281 | | | | | | | | |
| 201 | | 78.10 | 0.00 | 0.00 | 46.88 | 9.76 | 21.41 | 31.17 | 0.15 |
| 59.66 | 0.399 | | | | | | | | |
| 202 | | 78.10 | 0.00 | 0.00 | 36.06 | 25.55 | 16.46 | 42.01 | 1.43 |
| 644.76 | 0.538 | | | | | | | | |

 Node Depth Summary

| Node | Type | Average Depth | Maximum Depth | Maximum HGL | Time of Max Occurrence | Reported Max Depth |
|--------------|---------|---------------|---------------|-------------|------------------------|--------------------|
| | | Meters | Meters | Meters | days hr:min | Meters |
| Post_Saddler | OUTFALL | 0.00 | 0.00 | 0.00 | 0 00:00 | 0.00 |
| PostCtyRd | OUTFALL | 0.00 | 0.00 | 0.00 | 0 00:00 | 0.00 |
| Pre_CtyRd | OUTFALL | 0.00 | 0.00 | 0.00 | 0 00:00 | 0.00 |
| Pre_Saddler | OUTFALL | 0.00 | 0.00 | 0.00 | 0 00:00 | 0.00 |
| SU1 | STORAGE | 0.35 | 1.61 | 348.36 | 0 03:51 | 1.61 |

 Node Inflow Summary

| Node | Type | Maximum Lateral Inflow | Maximum Total Inflow | Time of Max Occurrence | Lateral Inflow Volume | Total Inflow Volume | Flow Balance Error |
|--------------|---------|------------------------|----------------------|------------------------|-----------------------|---------------------|--------------------|
| | | LPS | LPS | days hr:min | 10^6 ltr | 10^6 ltr | Percent |
| Post_Saddler | OUTFALL | 0.00 | 63.10 | 0 03:51 | 0 | 1.43 | 0.000 |
| PostCtyRd | OUTFALL | 59.66 | 59.66 | 0 03:06 | 0.147 | 0.147 | 0.000 |
| Pre_CtyRd | OUTFALL | 35.77 | 35.77 | 0 03:06 | 0.201 | 0.201 | 0.000 |
| Pre_Saddler | OUTFALL | 114.36 | 114.36 | 0 03:06 | 0.612 | 0.612 | 0.000 |
| SU1 | STORAGE | 644.76 | 644.76 | 0 03:00 | 1.43 | 1.43 | 0.000 |

 Node Surcharge Summary

No nodes were surcharged.

SADDLER STREET DEVELOPMENT – SWM MODELLING – 25 YEAR DESIGN STORM

 Node Flooding Summary

No nodes were flooded.

 Storage Volume Summary

| Storage Unit | Average Volume 1000 m ³ | Avg Pcmt Full | Evap Pcmt Loss | Exfil Pcmt Loss | Maximum Volume 1000 m ³ | Max Pcmt Full | Time of Max Occurrence days hr:min | Maximum Outflow LPS |
|--------------|---------------------------------------|---------------|----------------|-----------------|---------------------------------------|---------------|---------------------------------------|------------------------|
| SU1 | 0.149 | 8.1 | 0.0 | 0.0 | 0.805 | 43.8 | 0 03:51 | 63.10 |

 Outfall Loading Summary

| Outfall Node | Flow Freq Pcmt | Avg Flow LPS | Max Flow LPS | Total Volume 10 ⁶ ltr |
|--------------|----------------|--------------|--------------|-------------------------------------|
| Post_Saddler | 99.74 | 16.64 | 63.10 | 1.434 |
| PostCtyRd | 44.51 | 3.81 | 59.66 | 0.147 |
| Pre_CtyRd | 99.62 | 2.34 | 35.77 | 0.201 |
| Pre_Saddler | 99.98 | 7.08 | 114.36 | 0.612 |
| System | 85.96 | 29.86 | 265.63 | 2.393 |

 Link Flow Summary

| Link | Type | Maximum Flow LPS | Time of Max Occurrence days hr:min | Maximum Veloc m/sec | Max/ Full Flow | Max/ Full Depth |
|------|---------|--------------------|---------------------------------------|-----------------------|----------------|-----------------|
| OR1 | ORIFICE | 63.10 | 0 03:51 | | | 1.00 |

 Flow Classification Summary

| Conduit | Adjusted /Actual Length | Fraction of Time in Flow Class | | | | | | | |
|---------|-------------------------|--------------------------------|----------|----------|----------|---------|-----------|----------|------------|
| | | Up Dry | Down Dry | Sub Crit | Sup Crit | Up Crit | Down Crit | Norm Ltd | Inlet Ctrl |
| | | | | | | | | | |

 Conduit Surcharge Summary

No conduits were surcharged.

Analysis begun on: Wed Jan 17 20:47:25 2024
 Analysis ended on: Wed Jan 17 20:47:25 2024
 Total elapsed time: < 1 sec

SADDLER STREET DEVELOPMENT – SWM MODELLING – 50 YEAR DESIGN STORM

EPA STORM WATER MANAGEMENT MODEL - VERSION 5.2 (Build 5.2.4)

 Element Count

Number of rain gages 5
 Number of subcatchments ... 4
 Number of nodes 5
 Number of links 1
 Number of pollutants 0
 Number of land uses 0

 Raingage Summary

| Name | Data Source | Data Type | Recording Interval |
|--------------------------|--------------------------|-----------|--------------------|
| SCS_Type_II_39.8mm_2yr | SCS_Type_II_39.8mm_2yr | INTENSITY | 6 min. |
| SCS_Type_II_55.1mm_5yr | SCS_Type_II_55.1mm_5yr | INTENSITY | 6 min. |
| SCS_Type_II_78.1mm_25yr | SCS_Type_II_78.1mm_25yr | INTENSITY | 6 min. |
| SCS_Type_II_87.6mm_50yr | SCS_Type_II_87.6mm_50yr | INTENSITY | 6 min. |
| SCS_Type_II_97.1mm_100yr | SCS_Type_II_97.1mm_100yr | INTENSITY | 6 min. |

 Subcatchment Summary

| Name | Area | Width | %Imperv | %Slope | Rain Gage | Outlet |
|------|------|---------|---------|--------|-------------------------|-------------|
| 101 | 1.10 | 212.00 | 0.80 | 1.7000 | SCS_Type_II_87.6mm_50yr | Pre_CtyRd |
| 102 | 2.78 | 330.00 | 4.90 | 1.6000 | SCS_Type_II_87.6mm_50yr | Pre_Saddler |
| 201 | 0.47 | 212.00 | 12.50 | 2.8000 | SCS_Type_II_87.6mm_50yr | PostCtyRd |
| 202 | 3.41 | 1100.00 | 32.70 | 2.5000 | SCS_Type_II_87.6mm_50yr | SU1 |

 Node Summary

| Name | Type | Invert Elev. | Max. Depth | Ponded Area | External Inflow |
|--------------|---------|--------------|------------|-------------|-----------------|
| Post_Saddler | OUTFALL | 0.00 | 0.00 | 0.0 | |
| PostCtyRd | OUTFALL | 0.00 | 0.00 | 0.0 | |
| Pre_CtyRd | OUTFALL | 0.00 | 0.00 | 0.0 | |
| Pre_Saddler | OUTFALL | 0.00 | 0.00 | 0.0 | |
| SU1 | STORAGE | 346.75 | 2.75 | 0.0 | |

 Link Summary

| Name | From Node | To Node | Type | Length | %Slope | Roughness |
|------|-----------|--------------|---------|--------|--------|-----------|
| OR1 | SU1 | Post_Saddler | ORIFICE | | | |

 Cross Section Summary

| Conduit | Shape | Full Depth | Full Area | Hyd. Rad. | Max. Width | No. of Barrels | Full Flow |
|---------|-------|------------|-----------|-----------|------------|----------------|-----------|
| | | | | | | | |

 Analysis Options

 Flow Units LPS
 Process Models:

SADDLER STREET DEVELOPMENT – SWM MODELLING – 50 YEAR DESIGN STORM

```

Rainfall/Runoff ..... YES
RDII ..... NO
Snowmelt ..... NO
Groundwater ..... NO
Flow Routing ..... YES
Ponding Allowed ..... NO
Water Quality ..... NO
Infiltration Method ..... CURVE_NUMBER
Flow Routing Method ..... DYNWAVE
Surcharge Method ..... EXTRAN
Starting Date ..... 12/02/2023 00:00:00
Ending Date ..... 12/03/2023 00:00:00
Antecedent Dry Days ..... 0.0
Report Time Step ..... 00:01:00
Wet Time Step ..... 00:05:00
Dry Time Step ..... 00:05:00
Routing Time Step ..... 5.00 sec
Variable Time Step ..... YES
Maximum Trials ..... 8
Number of Threads ..... 1
Head Tolerance ..... 0.001524 m
    
```

```

*****
                Volume          Depth
Runoff Quantity Continuity  hectare-m          mm
*****
Total Precipitation .....    0.680          87.600
Evaporation Loss .....      0.000           0.000
Infiltration Loss .....     0.397          51.197
Surface Runoff .....        0.282          36.277
Final Storage .....         0.001           0.141
Continuity Error (%) .....  -0.017
    
```

```

*****
                Volume          Volume
Flow Routing Continuity    hectare-m          10^6 ltr
*****
Dry Weather Inflow .....    0.000           0.000
Wet Weather Inflow .....    0.282           2.819
Groundwater Inflow .....    0.000           0.000
RDII Inflow .....           0.000           0.000
External Inflow .....       0.000           0.000
External Outflow .....      0.282           2.818
Flooding Loss .....         0.000           0.000
Evaporation Loss .....      0.000           0.000
Exfiltration Loss .....     0.000           0.000
Initial Stored Volume ....  0.000           0.000
Final Stored Volume .....   0.000           0.001
Continuity Error (%) .....  0.000
    
```

```

*****
Time-Step Critical Elements
*****
None
    
```

```

*****
Highest Flow Instability Indexes
*****
All links are stable.
    
```

```

*****
Most Frequent Nonconverging Nodes
*****
Convergence obtained at all time steps.
    
```

```

*****
Routing Time Step Summary
*****
Minimum Time Step      :    4.50 sec
Average Time Step      :    5.00 sec
    
```

SADDLER STREET DEVELOPMENT – SWM MODELLING – 50 YEAR DESIGN STORM

```

Maximum Time Step      :      5.00 sec
% of Time in Steady State :      0.00
Average Iterations per Step :      2.00
% of Steps Not Converging :      0.00
Time Step Frequencies :
  5.000 - 3.155 sec   :    100.00 %
  3.155 - 1.991 sec   :      0.00 %
  1.991 - 1.256 sec   :      0.00 %
  1.256 - 0.792 sec   :      0.00 %
  0.792 - 0.500 sec   :      0.00 %
    
```

 Subcatchment Runoff Summary

| Peak Runoff | Runoff Coeff | Total Precip | Total Runon | Total Evap | Total Infil | Imperv Runoff | Perv Runoff | Total Runoff | Total Runoff |
|--------------|--------------|--------------|-------------|------------|-------------|---------------|-------------|--------------|--------------|
| Subcatchment | | mm | mm | mm | mm | mm | mm | mm | 10^6 ltr |
| LPS | | | | | | | | | |
| 101 | | 87.60 | 0.00 | 0.00 | 65.05 | 0.70 | 21.66 | 22.36 | 0.25 |
| 48.13 | 0.255 | | | | | | | | |
| 102 | | 87.60 | 0.00 | 0.00 | 60.72 | 4.29 | 22.34 | 26.64 | 0.74 |
| 146.41 | 0.304 | | | | | | | | |
| 201 | | 87.60 | 0.00 | 0.00 | 50.64 | 10.95 | 25.97 | 36.93 | 0.17 |
| 72.65 | 0.422 | | | | | | | | |
| 202 | | 87.60 | 0.00 | 0.00 | 39.04 | 28.66 | 19.88 | 48.54 | 1.66 |
| 756.00 | 0.554 | | | | | | | | |

 Node Depth Summary

| Node | Type | Average Depth | Maximum Depth | Maximum HGL | Time of Max Occurrence | Reported Max Depth |
|--------------|---------|---------------|---------------|-------------|------------------------|--------------------|
| | | Meters | Meters | Meters | days hr:min | Meters |
| Post_Saddler | OUTFALL | 0.00 | 0.00 | 0.00 | 0 00:00 | 0.00 |
| PostCtyRd | OUTFALL | 0.00 | 0.00 | 0.00 | 0 00:00 | 0.00 |
| Pre_CtyRd | OUTFALL | 0.00 | 0.00 | 0.00 | 0 00:00 | 0.00 |
| Pre_Saddler | OUTFALL | 0.00 | 0.00 | 0.00 | 0 00:00 | 0.00 |
| SU1 | STORAGE | 0.42 | 1.82 | 348.57 | 0 03:56 | 1.82 |

 Node Inflow Summary

| Node | Type | Maximum Lateral Inflow | Maximum Total Inflow | Time of Max Occurrence | Lateral Inflow Volume | Total Inflow Volume | Flow Balance Error |
|--------------|---------|------------------------|----------------------|------------------------|-----------------------|---------------------|--------------------|
| | | LPS | LPS | days hr:min | 10^6 ltr | 10^6 ltr | Percent |
| Post_Saddler | OUTFALL | 0.00 | 67.15 | 0 03:56 | 0 | 1.66 | 0.000 |
| PostCtyRd | OUTFALL | 72.65 | 72.65 | 0 03:06 | 0.174 | 0.174 | 0.000 |
| Pre_CtyRd | OUTFALL | 48.13 | 48.13 | 0 03:06 | 0.246 | 0.246 | 0.000 |
| Pre_Saddler | OUTFALL | 146.41 | 146.41 | 0 03:06 | 0.741 | 0.741 | 0.000 |
| SU1 | STORAGE | 756.00 | 756.00 | 0 03:00 | 1.66 | 1.66 | 0.000 |

 Node Surcharge Summary

No nodes were surcharged.

SADDLER STREET DEVELOPMENT – SWM MODELLING – 50 YEAR DESIGN STORM

Node Flooding Summary

No nodes were flooded.

Storage Volume Summary

| Storage Unit | Average Volume 1000 m ³ | Avg Pcmt Full | Evap Pcmt Loss | Exfil Pcmt Loss | Maximum Volume 1000 m ³ | Max Pcmt Full | Time of Max Occurrence days hr:min | Maximum Outflow LPS |
|--------------|---------------------------------------|---------------|----------------|-----------------|---------------------------------------|---------------|---------------------------------------|------------------------|
| SU1 | 0.192 | 10.5 | 0.0 | 0.0 | 0.961 | 52.4 | 0 03:56 | 67.15 |

Outfall Loading Summary

| Outfall Node | Flow Freq Pcmt | Avg Flow LPS | Max Flow LPS | Total Volume 10 ⁶ ltr |
|--------------|----------------|--------------|--------------|-------------------------------------|
| Post_Saddler | 99.76 | 19.22 | 67.15 | 1.657 |
| PostCtyRd | 44.82 | 4.48 | 72.65 | 0.174 |
| Pre_CtyRd | 99.05 | 2.88 | 48.13 | 0.246 |
| Pre_Saddler | 99.98 | 8.58 | 146.41 | 0.741 |
| System | 85.90 | 35.17 | 326.44 | 2.818 |

Link Flow Summary

| Link | Type | Maximum Flow LPS | Time of Max Occurrence days hr:min | Maximum Veloc m/sec | Max/ Full Flow | Max/ Full Depth |
|------|---------|--------------------|---------------------------------------|-----------------------|----------------|-----------------|
| OR1 | ORIFICE | 67.15 | 0 03:56 | | | 1.00 |

Flow Classification Summary

| Conduit | Adjusted /Actual Length | Fraction of Time in Flow Class | | | | | | | |
|---------|-------------------------|--------------------------------|----------|----------|----------|---------|-----------|----------|------------|
| | | Up Dry | Down Dry | Sub Crit | Sup Crit | Up Crit | Down Crit | Norm Ltd | Inlet Ctrl |
| | | | | | | | | | |

Conduit Surcharge Summary

No conduits were surcharged.

Analysis begun on: Wed Jan 17 20:48:08 2024
Analysis ended on: Wed Jan 17 20:48:08 2024
Total elapsed time: < 1 sec

SADDLER STREET DEVELOPMENT – SWM MODELLING – 100 YEAR DESIGN STORM

EPA STORM WATER MANAGEMENT MODEL - VERSION 5.2 (Build 5.2.4)

Element Count

Number of rain gages 5
Number of subcatchments ... 4
Number of nodes 5
Number of links 1
Number of pollutants 0
Number of land uses 0

Raingage Summary

| Name | Data Source | Data Type | Recording Interval |
|--------------------------|--------------------------|-----------|--------------------|
| SCS_Type_II_39.8mm_2yr | SCS_Type_II_39.8mm_2yr | INTENSITY | 6 min. |
| SCS_Type_II_55.1mm_5yr | SCS_Type_II_55.1mm_5yr | INTENSITY | 6 min. |
| SCS_Type_II_78.1mm_25yr | SCS_Type_II_78.1mm_25yr | INTENSITY | 6 min. |
| SCS_Type_II_87.6mm_50yr | SCS_Type_II_87.6mm_50yr | INTENSITY | 6 min. |
| SCS_Type_II_97.1mm_100yr | SCS_Type_II_97.1mm_100yr | INTENSITY | 6 min. |

Subcatchment Summary

| Name | Area | Width | %Imperv | %Slope | Rain Gage | Outlet |
|------|------|---------|---------|--------|--------------------------|-------------|
| 101 | 1.10 | 212.00 | 0.80 | 1.7000 | SCS_Type_II_97.1mm_100yr | Pre_CtyRd |
| 102 | 2.78 | 330.00 | 4.90 | 1.6000 | SCS_Type_II_97.1mm_100yr | Pre_Saddler |
| 201 | 0.47 | 212.00 | 12.50 | 2.8000 | SCS_Type_II_97.1mm_100yr | PostCtyRd |
| 202 | 3.41 | 1100.00 | 32.70 | 2.5000 | SCS_Type_II_97.1mm_100yr | SU1 |

Node Summary

| Name | Type | Invert Elev. | Max. Depth | Ponded Area | External Inflow |
|--------------|---------|--------------|------------|-------------|-----------------|
| Post_Saddler | OUTFALL | 0.00 | 0.00 | 0.0 | |
| PostCtyRd | OUTFALL | 0.00 | 0.00 | 0.0 | |
| Pre_CtyRd | OUTFALL | 0.00 | 0.00 | 0.0 | |
| Pre_Saddler | OUTFALL | 0.00 | 0.00 | 0.0 | |
| SU1 | STORAGE | 346.75 | 2.75 | 0.0 | |

Link Summary

| Name | From Node | To Node | Type | Length | %Slope | Roughness |
|------|-----------|--------------|---------|--------|--------|-----------|
| OR1 | SU1 | Post_Saddler | ORIFICE | | | |

Cross Section Summary

| Conduit | Shape | Full Depth | Full Area | Hyd. Rad. | Max. Width | No. of Barrels | Full Flow |
|---------|-------|------------|-----------|-----------|------------|----------------|-----------|
| | | | | | | | |

Analysis Options

Flow Units LPS
Process Models:

SADDLER STREET DEVELOPMENT – SWM MODELLING – 100 YEAR DESIGN STORM

```

Rainfall/Runoff ..... YES
RDII ..... NO
Snowmelt ..... NO
Groundwater ..... NO
Flow Routing ..... YES
Ponding Allowed ..... NO
Water Quality ..... NO
Infiltration Method ..... CURVE_NUMBER
Flow Routing Method ..... DYNWAVE
Surcharge Method ..... EXTRAN
Starting Date ..... 12/02/2023 00:00:00
Ending Date ..... 12/03/2023 00:00:00
Antecedent Dry Days ..... 0.0
Report Time Step ..... 00:01:00
Wet Time Step ..... 00:05:00
Dry Time Step ..... 00:05:00
Routing Time Step ..... 5.00 sec
Variable Time Step ..... YES
Maximum Trials ..... 8
Number of Threads ..... 1
Head Tolerance ..... 0.001524 m
    
```

```

*****
                Volume          Depth
Runoff Quantity Continuity  hectare-m          mm
*****
Total Precipitation .....      0.753          97.100
Evaporation Loss .....          0.000           0.000
Infiltration Loss .....          0.426          54.944
Surface Runoff .....            0.326          42.034
Final Storage .....             0.001           0.140
Continuity Error (%) .....      -0.019
    
```

```

*****
                Volume          Volume
Flow Routing Continuity    hectare-m          10^6 ltr
*****
Dry Weather Inflow .....          0.000           0.000
Wet Weather Inflow .....          0.327           3.267
Groundwater Inflow .....          0.000           0.000
RDII Inflow .....              0.000           0.000
External Inflow .....           0.000           0.000
External Outflow .....          0.327           3.266
Flooding Loss .....             0.000           0.000
Evaporation Loss .....           0.000           0.000
Exfiltration Loss .....          0.000           0.000
Initial Stored Volume ....          0.000           0.000
Final Stored Volume .....          0.000           0.001
Continuity Error (%) .....          0.000
    
```

```

*****
Time-Step Critical Elements
*****
None
    
```

```

*****
Highest Flow Instability Indexes
*****
All links are stable.
    
```

```

*****
Most Frequent Nonconverging Nodes
*****
Convergence obtained at all time steps.
    
```

```

*****
Routing Time Step Summary
*****
Minimum Time Step      :      4.50 sec
Average Time Step      :      5.00 sec
    
```

SADDLER STREET DEVELOPMENT – SWM MODELLING – 100 YEAR DESIGN STORM

```

Maximum Time Step      :      5.00 sec
% of Time in Steady State :      0.00
Average Iterations per Step :      2.00
% of Steps Not Converging :      0.00
Time Step Frequencies :
  5.000 - 3.155 sec   :    100.00 %
  3.155 - 1.991 sec   :      0.00 %
  1.991 - 1.256 sec   :      0.00 %
  1.256 - 0.792 sec   :      0.00 %
  0.792 - 0.500 sec   :      0.00 %
  
```

 Subcatchment Runoff Summary

| Peak Runoff | Runoff Coeff | Total Precip | Total Runon | Total Evap | Total Infil | Imperv Runoff | Perv Runoff | Total Runoff | Total Runoff |
|--------------|--------------|--------------|-------------|------------|-------------|---------------|-------------|--------------|--------------|
| Subcatchment | | mm | mm | mm | mm | mm | mm | mm | 10^6 ltr |
| LPS | | | | | | | | | |
| 101 | | 97.10 | 0.00 | 0.00 | 70.15 | 0.78 | 25.98 | 26.76 | 0.29 |
| 62.51 | 0.276 | | | | | | | | |
| 102 | | 97.10 | 0.00 | 0.00 | 65.26 | 4.76 | 26.84 | 31.60 | 0.88 |
| 183.12 | 0.325 | | | | | | | | |
| 201 | | 97.10 | 0.00 | 0.00 | 54.25 | 12.14 | 30.68 | 42.82 | 0.20 |
| 86.37 | 0.441 | | | | | | | | |
| 202 | | 97.10 | 0.00 | 0.00 | 41.73 | 31.76 | 23.60 | 55.36 | 1.89 |
| 873.54 | 0.570 | | | | | | | | |

 Node Depth Summary

| Node | Type | Average Depth | Maximum Depth | Maximum HGL | Time of Max Occurrence | Reported Max Depth |
|--------------|---------|---------------|---------------|-------------|------------------------|--------------------|
| | | Meters | Meters | Meters | days hr:min | Meters |
| Post_Saddler | OUTFALL | 0.00 | 0.00 | 0.00 | 0 00:00 | 0.00 |
| PostCtyRd | OUTFALL | 0.00 | 0.00 | 0.00 | 0 00:00 | 0.00 |
| Pre_CtyRd | OUTFALL | 0.00 | 0.00 | 0.00 | 0 00:00 | 0.00 |
| Pre_Saddler | OUTFALL | 0.00 | 0.00 | 0.00 | 0 00:00 | 0.00 |
| SU1 | STORAGE | 0.50 | 2.02 | 348.77 | 0 04:01 | 2.02 |

 Node Inflow Summary

| Node | Type | Maximum Lateral Inflow | Maximum Total Inflow | Time of Max Occurrence | Lateral Inflow Volume | Total Inflow Volume | Flow Balance Error |
|--------------|---------|------------------------|----------------------|------------------------|-----------------------|---------------------|--------------------|
| | | LPS | LPS | days hr:min | 10^6 ltr | 10^6 ltr | Percent |
| Post_Saddler | OUTFALL | 0.00 | 70.91 | 0 04:01 | 0 | 1.89 | 0.000 |
| PostCtyRd | OUTFALL | 86.37 | 86.37 | 0 03:06 | 0.202 | 0.202 | 0.000 |
| Pre_CtyRd | OUTFALL | 62.51 | 62.51 | 0 03:06 | 0.295 | 0.295 | 0.000 |
| Pre_Saddler | OUTFALL | 183.12 | 183.12 | 0 03:06 | 0.88 | 0.88 | 0.000 |
| SU1 | STORAGE | 873.54 | 873.54 | 0 03:00 | 1.89 | 1.89 | 0.000 |

 Node Surcharge Summary

No nodes were surcharged.

SADDLER STREET DEVELOPMENT – SWM MODELLING – 100 YEAR DESIGN STORM

Node Flooding Summary

No nodes were flooded.

Storage Volume Summary

| Storage Unit | Average Volume 1000 m ³ | Avg Pcmt Full | Evap Pcmt Loss | Exfil Pcmt Loss | Maximum Volume 1000 m ³ | Max Pcmt Full | Time of Max Occurrence days hr:min | Maximum Outflow LPS |
|--------------|---------------------------------------|---------------|----------------|-----------------|---------------------------------------|---------------|---------------------------------------|------------------------|
| SU1 | 0.241 | 13.1 | 0.0 | 0.0 | 1.127 | 61.4 | 0 04:01 | 70.91 |

Outfall Loading Summary

| Outfall Node | Flow Freq Pcmt | Avg Flow LPS | Max Flow LPS | Total Volume 10 ⁶ ltr |
|--------------|----------------|--------------|--------------|-------------------------------------|
| Post_Saddler | 99.77 | 21.92 | 70.91 | 1.890 |
| PostCtyRd | 44.68 | 5.22 | 86.37 | 0.202 |
| Pre_CtyRd | 98.04 | 3.48 | 62.51 | 0.295 |
| Pre_Saddler | 99.98 | 10.18 | 183.12 | 0.880 |
| System | 85.62 | 40.80 | 394.48 | 3.266 |

Link Flow Summary

| Link | Type | Maximum Flow LPS | Time of Max Occurrence days hr:min | Maximum Veloc m/sec | Max/ Full Flow | Max/ Full Depth |
|------|---------|--------------------|---------------------------------------|-----------------------|----------------|-----------------|
| OR1 | ORIFICE | 70.91 | 0 04:01 | | | 1.00 |

Flow Classification Summary

| Conduit | Adjusted /Actual Length | Fraction of Time in Flow Class | | | | | | | | |
|---------|-------------------------|--------------------------------|-----|------|------|------|------|------|----------|------------|
| | | Up | | Down | | Sub | | Sup | | |
| | | Dry | Dry | Dry | Crit | Crit | Crit | Crit | Norm Ltd | Inlet Ctrl |
| | | | | | | | | | | |

Conduit Surcharge Summary

No conduits were surcharged.

Analysis begun on: Wed Jan 17 20:49:17 2024
Analysis ended on: Wed Jan 17 20:49:18 2024
Total elapsed time: 00:00:01

Appendix C

BACKGROUND INFORMATION
PRE-CONSULTATION MEETING NOTES



TREMBLE PROPERTIES

PRE-CONSULTATION MEETING MINUTES

Project Nos. 6001, 1855, 6006

Date: Wednesday, August 17, 2022

Time: 10:00 a.m.

Place: Durham Arena

Attendees: Ms. Lorelie Spencer Municipality of West Grey
Mr. Scott Taylor County of Grey
Mr. Michael Cook SVCA
Mr. Jason Tremble Proponent
Mr. Donald Tremble Proponent
Mr. Travis Burnside Cobide Engineering
Ms. Dana Kieffer Cobide Engineering

Item

1. 221/ 229 Bruce St. S. Re-Development

Proposal:

A consent to create one residential lot, fronting onto Saddler St., 1 fourplex, fronting onto Bruce St. and 4 Consents to make the units freehold. A 40-unit apartment on the retained.

Applications needed:

- Consent for Saddler St. lot
- Rezone to R1
 - Minimum size reduction
- 4 consents for Bruce St. fourplex
- Rezone property to R3 to permit townhouses and apartment
 - Several site-specific permissions for the townhouses including: minimum lot size, maximum coverage, interior side yard
 - Potential site-specific amendment for height of the apartment building

Deliverables:

| <i>Required Information</i> | <i>Details</i> | <i>Action</i> |
|-----------------------------|---|---------------------------|
| Feasibility Study | Need elevation study, a maximum permitted depth | Cobide, to be included in |



TREMBLE PROPERTIES

PRE-CONSULTATION MEETING MINUTES

Project Nos. 6001, 1855, 6006

| | | |
|-------------------------------|---|---|
| | of 0.8 m for regional storm on Bruce St. to ensure safe access | submission |
| Record of Site Condition | Former contractors' yard, a phase 1 & 2 ESA has been completed, the consultant will register a RSC | Proponent/ Cobide, details to be included in submission |
| Functional Servicing Report | Municipality would like to see projected flows for sewage to ensure capacity | West Grey/ Cobide, discussion prior to submission |
| Stormwater Management | Cobide requesting clearance from SVCA that the property not have quantity control due to the direct outlet to the Saugeen River, but still propose to control quality | Cobide to follow up with E. Downing, SVCA |
| Planning Justification Report | Required | Cobide, to be included in submission |
| Holding Removal | Property has a H-Holding for a feasibility study for residential development | West Grey/ Cobide |

Other Notes:

- S. Taylor confirmed a condo exemption following a zoning by-law amendment would be acceptable.
- S. Taylor recommended engaging Saugeen Ojibway Nation
- L. Spencer mentioned that a turning radius for emergency services should be shown on the drawings at the time of Site Plan Approval.

2. Part Park Lot 5, Plan 505, Park St. Development

Proposal:



TREMBLE PROPERTIES

PRE-CONSULTATION MEETING MINUTES

Project Nos. 6001, 1855, 6006

Local Official Plan Amendment and Zoning By-law Amendment to permit a 59 unit apartment, 1 fourplex and 1 fiveplex (to be freehold)


419 Park: fiveplex, freehold

Applications needed:

- Local Official Plan Amendment from FD to Residential.
- Zoning By-law Amendment from FD to R3
 - Reductions for lot size and interior side yards, increase in coverage for proposed townhouses
- 5 Consents for 419 Park St.
- 9 Consents to create freehold townhouses located on adjacent parcel
- Rezone retained property to R3-H
 - Apartment building is conceptual at this time as more land in the area may be acquired.
 - Sewage allocation will need to be confirmed based on unit counts

Deliverables:

| <i>Required Information</i> | <i>Details</i> | <i>Action</i> |
|-----------------------------|---|--|
| Dry-Flood Proofing | Units 1-5 may need to be dry-flood proofed at time of construction depending on design. | Proponent , to decide on building design at time of construction and obtain SVCA permit as needed |
| Landfill | The property is 393 m from the landfill. | West Grey to provide details on landfill study Cobide to potentially confirm suitability of site for residential development based on information |
| Functional Servicing Report | Municipality would like to see projected flows for sewage to ensure capacity | West Grey/ Cobide , discussion prior to submission |
| Stormwater Management | Required | Cobide , to be included in |



TREMBLE PROPERTIES

PRE-CONSULTATION MEETING MINUTES

Project Nos. 6001, 1855, 6006

| | | |
|------------------------|---|--|
| | | submission |
| Planning Justification | Include notes on compatibility between the townhouses and the retained. Potential fencing required. Address servicing | Cobide , to be included in submission |

Other Notes:

- M. Cook confirmed an EIS was not required
- M. Cook confirmed safe access
- L. Spencer confirmed two fees will be required since they're two different properties.

3. Lambton/ Saddler St. Development

Proposal:

Plan of Subdivision to create 28 freehold townhouse units. Plan will include a Condominium block with 30 smaller home units on a private road.

Applications needed:

- Draft Plan of Subdivision
- Rezone to R3
 - Minimum size lot reduction
 - Minimum building size reduction for condo block
 - Potential lot coverage reduction
- Plan of Condominium Exemption

Deliverables:

| <i>Required Information</i> | <i>Details</i> | <i>Action</i> |
|--------------------------------|---|--|
| Grey County Highways exemption | Proposed new entrance onto Lambton St. (County Road 4) is within 400m of Rock St. | Grey County , to confirm this acceptable Grey County to confirm if road widening required |



TREMBLE PROPERTIES

PRE-CONSULTATION MEETING MINUTES

Project Nos. 6001, 1855, 6006

| | | |
|-------------------------------|--|---|
| Traffic Study | More than 50 units requires | Cobide , to be included in submission |
| EIS | Completed | Cobide , to be included in submission |
| Archeological study | Completed | Cobide , to be included in submission |
| Functional Servicing Report | Municipality would like to see projected flows for sewage to ensure capacity | West Grey/ Cobide , discussion prior to submission |
| Stormwater Management | Required | Cobide , to be included in submission |
| Planning Justification Report | To address compatibility between development and adjacent gravel pit | Cobide , to be included in submission |
| WHPA Clearance | Property is within a WHPA, clearance needed | Cobide , to be included in submission |

Other Notes:

Appendix D

**DESIGN DETAILS
OIL GRIT SEPARATOR (OGS)**

Hydro First Defense® - HC



Rev. 9.6

Project Name: **Saddler Street** Report Date:
 Street: **Saddler Street** City: **Durham**
 Province: **ON** Country: **Canada**
 Designer: **Travis Burnside** email:

Treatment Parameters:

Structure ID: **OGS**
 TSS Goal: **80 % Removal**
 TSS Particle Size: **Fine**
 Area: **3.4 ha**
 Percent Impervious: **33%**
 Rational C value: **0.66**
 Rainfall Station: **Owen Sound**
 Peak Storm Flow: **158 L/s**

| RESULTS SUMMARY | | |
|-----------------|--------------|--------------|
| Model | TSS | Volume |
| FD-3HC | 74.2% | 88.1% |
| FD-4HC | 78.2% | 95.9% |
| FD-5HC | 81.9% | 98.3% |
| FD-6HC | 84.3% | 98.9% |
| FD-8HC | 88.4% | 98.9% |

Model Specification:

Model: **FD-5HC**
 Diameter: **1500 mm**
 Peak Flow Capacity: **566.00 L/s**
 Sediment Storage: **0.84 m³**
 Oil Storage: **1136.00 L**

Installation Configuration:

Placement: **Online**
 Outlet Pipe Size: **375 mm** OK
 Inlet Pipe 1 Size: **375 mm** OK
 Inlet Pipe 2 Size: **mm** OK
 Inlet Pipe 3 Size: **mm** OK
 Rim Level: **350.420 m**
 Outlet Pipe Invert: **348.220 m** OK
 Invert Pipe 1: **348.260 m** OK
 Invert Pipe 2: **m**
 Invert Pipe 3: **m**

Designer Notes:


Net Annual Removal Model: FD-5HC

| Intensity ⁽¹⁾ | Fraction of Rainfall ⁽¹⁾ | FD-5HC Removal Efficiency ⁽²⁾ | Weighted Net Annual Efficiency |
|--------------------------|-------------------------------------|--|--------------------------------|
| (mm/hr) | (%) | (%) | (%) |
| 0.50 | 10.1% | 98.0% | 9.9% |
| 1.00 | 10.7% | 91.9% | 9.8% |
| 1.50 | 10.0% | 88.5% | 8.8% |
| 2.00 | 8.4% | 86.1% | 7.2% |
| 2.50 | 6.6% | 84.3% | 5.6% |
| 3.00 | 6.2% | 82.9% | 5.1% |
| 3.60 | 4.1% | 81.5% | 3.3% |
| 4.10 | 4.2% | 80.6% | 3.4% |
| 4.60 | 3.7% | 79.7% | 2.9% |
| 5.10 | 3.8% | 78.9% | 3.0% |
| 6.40 | 6.4% | 77.3% | 4.9% |
| 7.60 | 4.6% | 76.1% | 3.5% |
| 8.90 | 3.3% | 75.0% | 2.5% |
| 10.20 | 2.4% | 74.0% | 1.8% |
| 11.40 | 2.6% | 73.2% | 1.9% |
| 12.70 | 1.5% | 72.5% | 1.1% |
| 15.20 | 2.1% | 71.3% | 1.5% |
| 19.10 | 2.3% | 69.8% | 1.6% |
| 25.40 | 3.9% | 68.0% | 2.7% |
| 38.10 | 1.4% | 65.5% | 0.9% |
| 50.80 | 0.6% | 63.7% | 0.4% |

Total Net Annual Removal Efficiency: 81.9%
Total Annual Runoff Volume Treated: 98.3%

- Rainfall data based on 37 years of rainfall data for Canada Station Owen Sound, Owen Sound, Ontario, Canada.
- Based on third party verified data and approximating the removal of a PSD similar to the STC Fine distribution
- Rainfall adjusted to 5 min peak intensity based on hourly average.

Hydro First Defense® - HC



All drawing elevations are metres.

FD-5HC Specification

| | | |
|--------------------|---|---------------------|
| 1 | Vortex Chamber Diameter | 1500 mm |
| 2 | Inlet Pipe Diameter | 375 mm |
| 3 | Oil Storage Capacity | 1136.00 L |
| 4 | Min. Provided Sediment Storage Capacity | 0.84 m ³ |
| 5 | Outlet Pipe Diameter | 375 mm |
| 6 | Height(Final Grade to Outlet Invert) | 2200 mm |
| 7 | Sump Depth(Outlet Invert to Sump) | 1800 mm |
| Total Depth | | 4000 mm |

Notes:
